

4C/22 AWG STRANDED SHIELDED PLENUM
JACKET WHITE - 1000 FT SPOOL

SCP PART#:
22/4SHP

General Specification of Product :

Final Diameter : 0.155 inches 3.937 mm
Total Cable Weight : 25 kg/km 17 lbs/1000 ft
Conductor : 22 AWG 7 Strands of Bare Copper
Insulation : PVC Plenum
Shield : Alum Foil & Mylar Overall Shield
Drain \ Ground : 24 AWG 7 Strands of Tin Copper
Outer Jacket : PVC Plenum

Print Notes : Sequentially marked per 2FT (0 - Infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 22/4SHP --- (UL) CL2P/CL3P
E198137-SCP OR FPLP 75°C (UL) C(UL) CMP FT-6 SHIELDED 4/C 22 AWG
--- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C: 15 Ohms / 1000 ft
Mutual Capacitance : 49.3 pF/ft
Cond to Shield Cap. : 83 pF/ft
Impedance : 50 Ohms
Velocity of Prop : 56 %
Inductance. : 1.5 mH/km

Additional Information :

Cabled OD Avg: 0.116
Ins Thickness: 0.008
Jkt Thickness: 0.015
Certified: UL CL2P/CL3P OR FPLP / UL C(UL) CMP
Flame Rating: Plenum
Max Voltage: 300V
Packaging: Plywood Spool 10 x 7 x 5"
Packaging Weight: 17 lbs