

Specifications



Eaton CC6A13U

Eaton Cooper Power series deadbreak crimp connector, One-hole, 11/16", Pad: Aluminum, Sleeve: Aluminum, 1/0 AWG or kcmil, 2/0 AWG or kcmil, 70 mm² compact or solid, Metallic gray, Unthreaded aluminum compression connector, Length: 5.94"

General specifications

PRODUCT NAME	Eaton Cooper Power series deadbreak crimp connector
CATALOG NUMBER	CC6A13U
UPC	194006076319
PRODUCT LENGTH/DEPTH	1.37 in
PRODUCT HEIGHT	5.96 in
PRODUCT WIDTH	0.85 in
PRODUCT WEIGHT	0.882 lb
CERTIFICATIONS	Not Applicable

Additional Specifications	
NUMBER OF HOLES	One-hole
TYPE	Unthreaded aluminum compression connector

Conductor	
STRANDED OR COMPRESSED CONDUCTOR SIZE	1/0 AWG

Dimensions	
OVERALL LENGTH	5.94"

Resources	
CATALOGS	600 A 15 and 25 kV class deadbreak accessories, tools, and replacement parts
SPECIFICATIONS AND DATASHEETS	Line installation and protective equipment specifiers guide Eaton Specification Sheet - CC6A13U
TECHNICAL DATA SHEETS	Aluminum and coppertop compression connector 600 A crimp chart

Application	
APPLICATION	600A Deadbreak Bol-T
SUITABLE FOR AL/ST-CABLES	Aluminum and copper cables

Descriptions	
COLOR	Metallic gray
CONNECTION	Compression
MATERIAL TYPE	Aluminum
NUMBER OF HOLES	One-hole
PAD MATERIAL	Aluminum
SLEEVE MATERIAL	Aluminum
STUD/BOLT SIZE	11/16"

Electrical Ratings	
CURRENT RATING	600A

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

