

# Kellems Wire Management, Deluxe Cord Grips, Straight Male, .875-1.000", 1", with Mesh

By Hubbell Wiring Device-Kellems  
Catalog # [07401025](#)

Kellems Wire Management, Deluxe Cord Grips, Straight Male, .875-1.000", 1", with Mesh



## Application

- Straight Male- Form 4

## General

Color	
EU RoHS Indicator	Yes
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Sealing Ring Between Box And Fitting.
Item Type	Deluxe Cord Grips
Material	Aluminum Fittings, Stainless Steel Mesh
Material - Mounting Hardware	Locknut or Tapped Opening
Operating Temperature	-30°F to +240°F (-34°C to +115°C)
Performance	<ul style="list-style-type: none"><li>• Environmental - Flammability - UL 94HB (Strand grip), UL 94V-2(Fitting)</li><li>• Environmental - Hazardous Locations - Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 &amp; 2, Class III Div. 1 &amp; 2 N.E.C</li><li>• Environmental - Operating Temperatures - -30°F to +240°F (-34°C to +115°C)</li><li>• Environmental - Wet Locations - Suitable for use in wet locations when used with a listed sealing ring between box and fitting</li></ul>
Series	Deluxe Cord Grips
Style	For Insulated Cables
Temperature Rating	Minimum -30 Deg F to 240 Deg F (-34 Deg C to 115 Deg C)
Thread Size	1" NPT
Type	Straight Male Thread
UPC	783585322063

## Dimensions

Display Size	1" NPT
Weight	0.3 lb

## Conductor Related

Cable Diameter Range	0.875 in-1.000 in
Cable Size	.875"-1.000" (2.22-2.54)
Conductor Range	0.875-1 in (2.22-2.54 mm)
Number of Conductors	Single

## Certifications And Compliance

Industry Standard(s)	UL Listed
Standards - RoHS Compliance Status	CM

## Logistics

Carton Quantity	5
Pallet Quantity	1500

## Product Assets

[Catalogs - WDK Catalog Full 2024](#)  
[Literature - Wire Management Solutions Brochure](#)  
[Warranty - Industrial & Commercial Products](#)



