

Specifications



Photo is representative



Eaton 301-82

Eaton Cooper Power series ultra range copper squeezer connectors, Cmprsn, 2 Cndtrs, CU, Grv A #4 - #8 sol, Grv B #4 - #8 sol, Wire mx A .204 in., Wire mn A .128 in., Wire mx B .204 in., Wire mn B .128 in., B-K-T, KBKT (Burndy), 3, 1 indents

General specifications

PRODUCT NAME	Eaton Cooper Power series ultra range copper squeezer connectors
CATALOG NUMBER	301-82
UPC	194006029728
PRODUCT LENGTH/DEPTH	0.781 in
PRODUCT HEIGHT	1.07 in
PRODUCT WIDTH	0.53 in
PRODUCT WEIGHT	0.22 lb
CERTIFICATIONS	Not Applicable



Powering Business Worldwide

Conductor	
CONDUCTOR RANGE GROOVE A	#4 - #8 sol
CONDUCTOR RANGE GROOVE B	#4 - #8 sol
NUMBER OF CONDUCTORS	2

Wire description	
WIRE RANGE DIAMETER GROOVE A - MAX	0.204 in
WIRE RANGE DIAMETER GROOVE A - MIN	0.128 in
WIRE RANGE DIAMETER GROOVE B - MAX	0.204 in
WIRE RANGE DIAMETER GROOVE B - MIN	0.128 in

Description	
CONNECTION	Compression
DIE	B-K-T, KBKT (Burndy)
MATERIAL TYPE	Copper
NUMBER OF INDENTS	3, 1
TYPE	Ultra range copper Squeezon connectors

Resources	
CATALOGS	Kearney Connectors Tee-Tap Terminal and Cast Stirrups Catalog
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 301-82 Overhead line installation and protective equipment specifiers guide

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. Follow us on social media to get the latest product and support information.
All other trademarks are property of their respective owners.

