




**HSC14FR, Heat Shrink Tubing,
0.25" ID Min.(Exp.), 0.125" ID Max.
(Rec.), 12-10 Flex, PVC, Flame
Retardant, Clear, 600V.**

By Burndy
Catalog # [HSC14FR](#)



Heat Shrink Tubing, 0.25" ID Min.(Exp.), 0.125" ID Max.(Rec.),
12-10 Flex, PVC, Flame Retardant, Clear, 600V.

Application

For Terminations And Splices

General

Color	Clear
Connector Type	CLEAR TUBES
EU RoHS Indicator	Yes
Material	Polyvinyl chloride
Sub Brand	VISISHRINK
Trade Name	VISI-SHRINK™
Type	HSC-FR, Thin Wall, Flexible, Fire Retardant
UPC	781810266199

Conductor Related

Conductor Range	#12 AWG to #10 AWG
Conductor Size	12AWG -8AWG

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

- [Catalogs - Full Line BURNDY Catalog](#)
- [Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing](#)
- [Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide](#)
- [Sales Drawings - 50015598](#)
- [Video - Heat Shrink Product Overview & Installation](#)



A proud member of the Hubbell Family.