

Notorious

Porcelain Stone[®]

Colors



NTR01 ▶ Femme Fatal



NTR02 ▶ Private Eye



NTR03 ▶ Sugar Daddy



NTR04 ▶ Suspense



NTR05 ▶ Leading Man



NTR06 ▶ Film Noir

Features and Benefits

- Distinct concrete visuals deliver urban sophistication with a level of endurance true concrete can't offer.
- Modular sizing, mosaics, and brick plank looks to trim including a cove base and bullnose
- Complete trim package including mosaics suitable for shower floors
- All field tile is rectified and modular with a minimum of 3mm grout joint
- Cross-Sheen finish for easy cleaning
- Contains a minimum of 4% pre-consumer recycled content and is manufactured by Crossville[®] using processes that are Green SquaredSM certified
- Perfectly blend with Crossville's Nest wood-look porcelain for even more solutions. Wrap concrete with planks for a new take on parquet
- Plank shapes are also available through Crossville's Get Planked[®] program, which offers a variety of plank sizes with no minimum order and a short lead time



Notorious

Porcelain Stone[®]

Sizes (Shown in NTR04)



Mosaics
UPS Finish
(Mounted on an
12 x 12 sheet.)

Get Planked!

Our Porcelain Stone[®] products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



Sizes & Finishes

Field Tile

Available in all colors

Nominal (in)	Actual (mm)	Thickness (mm)	Finish
3 x 15	72 x 372	10.5	UPS
12 x 12	297 x 297	10.5	UPS/HON
12 x 24	297 x 597	10.5	UPS/HON
24 x 24	597 x 597	10.5	UPS/HON
24 x 36	597 x 897	10.5	UPS/HON

Crossville recommends a grout joint of 3mm
Actual measurements stated in inches indicate tile is calibrated (non-rectified).
Actual measurements stated in mm indicate tile is rectified.

Mosaics

Available in all colors


Nominal (in)	Actual (in)	Thickness (mm)	Finish
Mosaic*	12 x 12	10.5	UPS

*Mounted on 12 x 12 sheet

Coordinating Trim

Nominal (mm)	Actual (mm)	Thickness (mm)	Finish
4 x 12 Single Bullnose	97 x 297	10.5	UPS/HON**
6 x 12 Cove Base	150 x 297	10	UPS

**HON finish is special order only



Product Performance


Breaking Strength	>500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UPS	0.50 - 0.60	AcuTest SM
HON	0.42 - 0.52	AcuTest SM

Shade & Texture Index

Notorious has a shade variation of V2.



This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.



Notorious

Crossville, Inc.

PO Box 1168
Crossville, TN
38557

Phone 931.484.2110
Fax 931.456.2956
E-Mail Crossc@CrossvilleInc.com
Web CrossvilleInc.com

Recommended Use

Notorious is recommended for interior floors, walls, counter tops and exterior walls in both residential and commercial applications. If offset pattern is required for tiles 18 inches or longer, Crossville® recommends an offset of not greater than 33%. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage. See CrossvilleInc.com for detailed installation instructions.

Care and Maintenance

Regular cleaning is the best way to keep Notorious tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More Information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.



NTR05 ▶ Leading Man 24 x 36 UPS on floor
Laminam by Crossville ▶ Calce Grigio on bar

Hydrotect™

Our porcelain tiles are available with Hydrotect™. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at CrossvilleInc.com.



EcoCycle Tile Process™

Notorious contains a minimum of 4 percent pre-consumer recycled content and is manufactured by Crossville® using processes that recycle nearly 12 million pounds of previously discarded filtrate and fired tile waste. In addition to its own fired waste recycling, Crossville also accepts and recycles reclaimed, previously installed tile through its Tile Take-Back™ Program. For more information, visit CrossvilleInc.com/green.

Green Squared™ Certified

Crossville® has earned Green Squared™ certification from the Tile Council of North America (TCNA) for its entire U.S.-manufactured porcelain product line-up, as well as its manufacturing processes. The company is among the first ever recipients of this certification standard for the tile industry. TCNA developed the Green Squared certification under American National Standards Institute (ANSI) process. The multi-attribute program (ANSI A138.1) scores products in five categories of performance: product characteristics, manufacturing, corporate governance, innovation and end-of-life. Crossville's certified products and processes received stringent evaluation from Scientific Certification Systems (SCS), the green building industry's longest standing third-party certifier.

National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

Exterior Cladding

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-to-zero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

▶▶ Crossville® Sample Express

Sample fulfillment & Help Line
Samples@CrossvilleInc.com
1 800 221.9093

Loose Samples for
Architects & Designers

Loose Tile Samples
Sizes may vary depending on product series
Max. of 4 large field tile per order

Replacement Chips for PSS Rack
Max. of 5, 2 x 2 chips per color

Standard Shipping
UPS Ground

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

Trade Organizations



Environmentally Aware

