



SP-90 SILICONE LUBRICANT SPRAY

SP-90 is a precision silicone-based general-purpose lubricant. The “dry” film provides an even coverage and maximum lubrication without staining. A highly versatile product that is an excellent performance lubricant and release agent. Wide temperature range: -50°C to +200°C. Good materials compatibility.

KEY FEATURES

- Dry film precision silicone lubricant
- Lubricates and reduces friction
- Effective temperature range: -50°C to +200°C
- Solvent free formulation
- Safe for use on all metals, most rubbers and most plastics

MARKET SECTORS:

TRADE/PRO-DIY

ENGINEERING

FASTENERS & FIXINGS

ELECTRICAL MRO

AGRICULTURE

AC CODE	CRC CODE	SIZE
-	33319	500ml Aerosol TwinSpray
1887	32773	500ml Aerosol

NEVER ASK A PROFESSIONAL TO USE ANYTHING ELSE!

APPLICATION AREAS

Use in numerous application areas throughout the electrical, plastic processing, plumbing, metal working and sewing/upholstery industries. SP-90 effectively lubricates plastic to plastic contact surfaces, sewing needles and other rapidly oscillating components, O-rings and assists with the installation of cabling.

DIRECTIONS FOR USE

- Shake the can before use.
- Spray a light, even film on areas requiring lubrication or protection.
- Repeat application if necessary.
- Harmless to most commonly used rubbers and plastics, if in doubt please test prior to use (not suitable for use on silicone rubbers).
- Do not use on live electrical equipment.

APPEARANCE:	Clear, colourless oil
ODOUR:	Odourless
SPECIFIC GRAVITY AT 20°C:	0.970
TEMPERATURE RANGE:	-50 °C to 200 °C
SOLUBILITY:	Insoluble in water

(All values apply to product without aerosol propellant)

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from <https://www.actioncan.com/product/sp-90/> or from info.uk@crcind.com

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.

