


## QX630QT DATA SHEET

## TECHNICAL SPECIFICATIONS



SKU Tweeter

Woofer (2) 6.5" (165mm) Aluminum

Frequency Response 65Hz-24kHz +/-3dB

Nominal Impedance 4 ohms

**Recommended Power Range** 50 watts minimum; 200 watts maximum

**QX630QT** 

60646 - Each

Quadratech 0.75" (19mm) four titanium dome Tweeter. Ferrofluid-cooled

Sensitivity (2.83V/1m) 94dB SPL Crossover 2-way

Average Coverage Angle 108 Degrees Horizontal; 67 Degrees

Vertica

Enclosure Aircraft Marine Grade Aluminum

**Finishes** White Paintable Grille (Paintable By

Request Only)

**Cut-Out Dims (WxH)** 8.91" x 21.5" (226.31mm x 546.1mm)

Required Mounting Depth (D) 3.875" (98.42mm)

Overall Dimensions (WxHxD) 9.61" x 22.2" x 4.125" (244.09mm x 563.88mm x 104.77mm)

**Grille Dimensions (WxH)** 9.61" x 22.2" (244.09mm x 563.88mm)

For indoor use; Available as Marine Grade,

must specify when ordering

# 3.875" Mour **Bot**

3.875" (98.42mm) Mounting Depth **Bottom View** 

## **QX630QT IN-WALL ACCESSORIES**

### QX630PB

Steel Pre Construction Board | 60183

### QX630PBF

MDF Flush-Mount Pre Construction Board | 60182

James by Sonance warrants this product to the original purchaser to be free from defects in materials and workmanship under normal use. Limited Lifetime Warranty applies to indoor installations. Limited Five (5) Year Warranty applies to outdoor or moisture-dense environments (e.g., spas, showers, saunas). Grille is warranted for five (5) years for both indoor and outdoor use. Warranty valid only for products purchased from authorized dealers and installed per manufacturer guidelines. Excludes damage from misuse, accidents, modifications, improper installation, or normal wear. For details or claims, visit sonance.com/company/contact

**Environment**