



T-511G

Swing, Y-Pattern, Threaded Connection, 300 WOG, Class 150



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-303G	1/2"	60	10	34
105-304G	3/4"	40	10	36
105-305G	1"	30	10	40
105-306G	1-1/4"	20	5	39
105-307G	1-1/2"	16	4	41
105-308G	2"	8	2	32

- Dezincification Resistant Bronze
- Can be Installed in Vertical or Horizontal Positions
- Residential and Commercial Applications
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



S-511G

Swing, Y-Pattern, Solder Connection, 300 WOG, Class 150



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-403G	1/2"	60	10	31
105-404G	3/4"	40	10	36
105-405G	1"	30	10	41
105-406G	1-1/4"	20	5	41
105-407G	1-1/2"	16	4	41
105-408G	2"	8	2	34

- Dezincification Resistant Bronze
- Can be Installed in Vertical or Horizontal Positions
- Residential and Commercial Applications
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content

