

# CyberPower

## P1004UC

### ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower P1004UC 10-outlet surge protector with USB ports offers a high level of surge protection for common home and office electronics such as computers and peripherals, home theater equipment, and appliances. With 3600 joules of surge protection, the P1004UC prevents power surges and power spikes caused by storms and grid fluctuations from reaching and harming your electronic equipment. In addition to surge protection, the CyberPower P1004UC can directly charge USB-enabled devices with one USB-A port rated at 2.4 amps output, and one 15 watt USB-C charging port. The P1004UC comes with 10 standard, grounded power outlets and a four-foot power cord with a low profile plug, which fits tightly against walls for placement behind furniture.

Features of the P1004UC include automatic shutdown, metal oxide varistor (MOV) technology, an EMI/RFI noise filter, keyhole mounting slots, and an impact-resistant casing. This surge suppressor comes with a One-Year Limited Warranty and a Connected Equipment Guarantee.

#### TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

#### FEATURES

- AC Outlets: 10
- AC Outlet Type: NEMA 5-15R
- Surge Protection: 3600 J
- USB-A Ports: 1
- USB-A Output: 2.4A
- USB-C Ports: 1
- USB-C Output: 15W
- Cord Length: 4-ft
- Plug Type: NEMA 5-15P
- Plug Style: Flat
- Electrical Rating: 125V/15A/60Hz
- Connected Equipment Guarantee: \$300,000
- Warranty: One-Year Limited Warranty



## SPECIFICATIONS

INPUT	
Circuit Breaker	15A
Cord Length	4 ft (1.2 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15A
Plug Style	45° Offset Right

OUTPUT	
Outlet Type	10 x NEMA 5-15R
Outlets - Total	10
Output Voltage	125 VAC
Output Watts - Continuous	1875 W
USB Charge Port Amperage	2.4 A (shared)
USB Charge Ports	1 x USB-C 1 x USB-A
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	15 Watts

P1004UC

ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	600V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	105,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	75,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	3600 J
PHYSICAL	
Color	White
Form Factor Supported	Keyhole (Wall Mount or Under-counter Installation)
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	9.4 x 4.09 x 28.04 cm
Physical Dimensions - Width/Height/Depth (mm)	94 x 41 x 280 mm
Physical Dimensions - Width/Height/Depth (in.)	3.7 x 1.61 x 11.04 in.
Weight (kg)	0.59 kg
Weight (lb)	1.30 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	16.19 x 35.56 x 5.08 cm
Shipping Dimensions - Width/Height/Depth (mm)	161.93 x 355.6 x 50.8 mm
Shipping Dimensions - Width/Height/Depth (in)	6.375 x 14 x 2 in.
Shipping Weight (kg)	0.64 kg
Shipping Weight (lbs.)	1.40 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363 UL1449 4th Edition UL1310 cUL
WARRANTY	
CEG Amount	\$300,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited