



FABRIC LOOK



INFUSION™

Your unique vision will come to life with Infusion™, using modular tiles that promote patterns using multiple sizes. Create seamless spaces and minimize grout joints with Infusion's full trim package and rectified edges featuring TruEdge™ technology. Versatile design will take the stage with a supporting cast of revered durability and modern style that can be used on the floor and wall.

Cover photo features White Wenge and Grey Wenge 12 x 24 on the floor.
Above photo features Taupe Fabric 12 x 24 on the floor.

INFUSION™

COLORBODY™ PORCELAIN FLOOR

AMERICAN OLEAN®

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



SEE CHARTS FOR FULL PRODUCT DETAILS.

FABRIC LOOK

COLORBODY™ PORCELAIN FLOOR TILE - FABRIC



WHITE FABRIC IF50



BEIGE FABRIC IF51



TAUPE FABRIC IF52



GRAY FABRIC IF55

COLORBODY™ PORCELAIN FLOOR TILE - WENGE



WHITE WENGE IF60



BEIGE WENGE IF61



TAUPE WENGE IF62



GRAY WENGE IF65



VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE

USAGE




MATERIAL



PRICING



SPECIAL FEATURES



SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	12 x 24 Floor Tile	11-3/4" x 23-1/2" (29.80 cm x 59.80 cm)	3/8"	11.69	6

LINEAR EXPRESS™ SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	6 x 24 Floor Tile	5-3/4" x 23-1/2" (14.60 cm x 59.80 cm)	3/8"	10.65	11
	4 x 24 Floor Tile	3-13/16" x 23-1/2" (9.70 cm x 59.80 cm)	3/8"	6.46	10
	2 x 24 Floor Tile	1-13/16" x 23-1/2" (4.70 cm x 59.80 cm)	3/8"	6.66	20

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

FEATURES



REVEAL IMAGING®



All or select items within this series meet the requirements for these qualifications.
For more information visit americanolean.com.

FABRIC LOOK

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose+†	4 x 12	S44C9	30
	Cove Base+†	6 x 12	S36C9T	30
	Cove Base Outercorner+†	6 x 1	SC36C9T	15

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

* Available in Fabric finish only.

† Coordinates with both Fabric and Wenge floor tile.

INSTALLATION

Grout Joint Recommendation	Shade Variation
<p>Floor: 3/16" (Overlap should not exceed 33% when installing tile with length 15" or greater in a staggered brick-joint pattern.)</p>	 MEDIUM (V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

