

Discover the serene sensibilities of Agio™, a tile that artfully depicts the weathered wonder of clay in wilderness-inspired hues. Featuring a wide variety of alluring colors, five sizes, including an on-trend 2" x 47", and three fashion-forward deco's, this collection is sure to enliven any space. Mix and match for endless possibilities for floor and wall designs that soothe the soul.

AGIO™
Glazed Porcelain





LARGE FORMAT FLOOR / WALL RESIDENTIAL COMMERCIAL INDOOR

Bianco**

Erba

Knit Bianco

Knit Erba

Dutti Deco

Linea Deco

Frassino**

Menta

Knit Frassino

Knit Menta

Herbar Deco

Ovale Deco

Affum**

Rino

Knit Affum

Knit Rino

Impianti Deco

Equ Deco

Corda**

Granata

Knit Corda

Knit Granata

Ura Deco

Vaso**

Senape

Knit Vaso

Knit Senape

Duna**

Turchino

Knit Duna

Knit Turchino

Noga

Petro

Knit Noga

Knit Petro

Lava**

Knit Lava

Knit Available in Slim Only:
12"x24" & 24"x47"

Knit Pattern



24"x47" Slim:

Dutti Deco

Herbar Deco

Impianti Deco

Linea Deco

Ovale Deco

Equ Deco

Sizes									
	47" x 109" Slim 47.09" x 109.25"	47" x 47" 47.09" x 47.09"	24" x 47" 23.50" x 47.09"	24" x 47" Slim 23.50" x 47.09"	24" x 24" 23.50" x 23.50"	12" x 24" Slim 11.71" x 23.50"	2" x 47" Slim 2.09" x 47.09"	1" x 6" Stacked Mosaic 12" x 12" Mesh 11.73" x 11.73"	3" x 12" Floor SBN
Thickness	6.5mm	10mm	10mm	6.5mm	6.5mm	6.5mm	6.5mm	6.5mm	Check Website
Faces	6	6	12	12 (Solid) 2 (Decos)	6	N/A	N/A	N/A	N/A
Finish	Matte	Matte	Matte	Matte	Matte	Matte	Matte	Matte	Matte
Edge	Rectified	Rectified	Rectified	Rectified	Rectified	Rectified	Rectified	Rectified	Cut/Rounded
Grout Joint Recommendation	1/8"	1/8"	1/8"	1/8"	1/8"	1/8"	1/8"	1/8"	Check Website
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A1371	Scratch Hardness MOHS	Shade Variation Rating	**47"x47" and 24"x47" 10mm only available in Duna, Lava, Bianco, Frassino, Affum, Corda, and Vaso.	
Results*	Class III	>350	Resistant	<0.5%	>0.42	5	V1		

- Sustainability Attributes
- Red List Free
 - Health Product Declaration (HPD) provided upon request
 - Product Packaging is 100% recyclable

Product and Installation Details | ANSI A108.02 Section 4.3.8.2 - For running bond/brick joint patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



*For more information visit www.emser.com. Always consult a professional for proper usage and installation.