

MIC® Tight-Buffered, Interlocking Armored Cable, Plenum 6 F, 50 μm multimode (OM4)



Part Number:
006T88-31190-A3

Corning MIC® interlocking armored plenum cables are designed for use in plenum, riser and general purpose environments for intrabuilding backbone and horizontal installations. These multifiber cables use individually jacketed 900 μm buffered fibers enabling easy, consistent stripping and facilitating termination. The fibers are grouped into jacketed subunits and surrounded by a dielectric central member. The core is protected by a flexible, spirally wrapped, aluminum interlocking armor that offers easy, one-step installation and up to seven times the crush protection of unarmored cables. With a flame-retardant outer jacket, this cable is particularly useful for heavy traffic or more challenging mechanical exposure conditions and applications requiring extra rugged cables.

Features and Benefits

Flexible, interlocking armor design



Seven times crush protection compared to non-armored cables

TBII buffered fibers

Easy, consistent stripping

Flame-retardant jacket

Rugged and durable



MIC® Tight-Buffered, Interlocking Armored Cable, Plenum 6 F, 50 µm multimode (OM4)

CORNING

Specifications

General Specifications

Environment	Indoor
Cable Type	Tight-Buffered
Product Type	Interlocking Armor
Fiber Category	50 µm MM (OM4)
Flame Rating	Plenum (OFCP)
Application	General Purpose Horizontal, Plenum, Vertical Riser
Fiber Count	6

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	National Electrical Code® (NEC®) OFCP, CSA FT-6, ICEA S-83-596

Environmental Conditions

Temperature Range, Installation	0 °C to 60 °C (32 °F to 140 °F)
Temperature Range, Operation	0 °C to 70 °C (32 °F to 158 °F)
Temperature Range, Storage	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design

Central Element	Yarn
Fiber Count	6
Number of Ripcords	2
Outer Jacket Color	Aqua
Outer Jacket Material	Flame-retardant
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members
Inner Jacket Material	Flame-retardant

MIC® Tight-Buffered, Interlocking Armored Cable, Plenum 6 F, 50 µm multimode (OM4)



Cable Design	
Tensile Strength Elements and/or Armoring - Layer 3	Interlocking Armor
Tight Buffer Color	Blue, Orange, Green, Brown, Slate, White
Flame Rating	Plenum (OFCP)

Mechanical Specifications	
Max. Tensile Strength, Long-Term, ≤12F	132 N (29.67 lbf)
Max. Tensile Strength, Long-Term, >12F	200 N (44.96 lbf)
Max. Tensile Strength, Long-Term	132 N (29.67 lbf)
Max. Tensile Strength, Short-Term, ≤12F	440 N (98.92 lbf)
Max. Tensile Strength, Short-Term, >12F	660 N (148.37 lbf)
Max. Tensile Strength, Short-Term	440 N (98.92 lbf)
Min. Bend Radius Installation	170 mm (6.69 in)
Min. Bend Radius Operation	113 mm (4.45 in)
Nominal Inner Cable Diameter	5.2 mm (0.2 in)
Nominal Outer Diameter	11.3 mm (0.44 in)

Optical Characteristics	
Fiber Code	T
Fiber Type	Multimode
Performance Option Code	90
Fiber Core Diameter	50 µm
Minimum Effective Modal Bandwidth (EMB)	4700 MHz*km / -
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Min. Overfilled Launch (OFL) Bandwidth	3500 MHz*km / 500 MHz*km
Serial 1 Gigabit Ethernet	1000 MHz*km / 600 MHz*km
Serial 10 Gigabit Ethernet	550 MHz*km / -
Wavelengths	850 nm / 1300 nm
Fiber Category	OM4

MIC® Tight-Buffered, Interlocking Armored Cable, Plenum 6 F, 50 μm multimode (OM4)



Ordering Information	
Product Number	006T88-31190-A3
EAN Code	4056418176765
Weight	103 kg/km (69.21 lb/1000 ft)



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2023 Corning Optical Communications. All rights reserved.