

Inspired by woven textiles, Thread II™ offers a subtle color palette with coordinating mosaics.

# THREAD II™


*Glazed Porcelain*

FLOOR / WALL  RESIDENTIAL  COMMERCIAL  INDOOR  POOL 






White

Mosaics



White

|                            |   |   |   |                          |                    |                          |                           |
|----------------------------|---|---|---|--------------------------|--------------------|--------------------------|---------------------------|
| Sizes                      |  |  |  |                          |                    |                          |                           |
|                            | 12" x 24"<br>11.81" x 23.62"  | 12" x 12" Mesh<br>11.81" x 11.81"   | 3" x 12"<br>Floor SBN   |                          |                    |                          |                           |
| Thickness                  | 9mm   | 9mm   | 9mm   |                          |                    |                          |                           |
| Faces                      | 1   | N/A   | N/A   |                          |                    |                          |                           |
| Finish                     | Matte   | Matte   | Matte   |                          |                    |                          |                           |
| Edge                       | Rectified   | Cut   | Cut/Rounded   |                          |                    |                          |                           |
| Grout Joint Recommendation | 1/8"  | Check Website   | Check Website   |                          |                    |                          |                           |
| Testing                    | Abrasion Resistance<br>C1027  | Breaking Strength<br>C648   | Chemical Resistance<br>C650   | Water Absorption<br>C373 | DCOF ANSI<br>A1371 | Scratch Hardness<br>MOHS | Shade Variation<br>Rating |
|                            | III   | >325 lbf  | Resistant   | <0.50%                   | >0.42              | 7                        | V1                        |

**Product and Installation Details | ANSI A108.02**  
 Section 4.3.8.2 - For running bond/brick jointing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



 Sustainability Attributes

- Red List Free
- Health Product Declaration (HPD) provided upon request
- Product Packaging is 100% recyclable
- VOC Free
- 0% Pre- & Post-Consumer

\*For more information visit [www.emser.com](http://www.emser.com). Always consult a professional for proper usage and installation.