

SUPPLY

DRAINAGE

SUPPORT

APPENDIX



638X208



643X208

PowerPEX™

Bullet™

Spin Closed Stub Out

- Type L copper

Bracketed Stub Out

- Perfect for stubbing up through floor for closets or lavs
- Square O Strap is crimped to tube 8" from spin closed end on 638X212E
- Type L copper

Open Ended Stub Out

- Type L copper

Item No	Connection	CTS	Length	Pkg	Min Qty	Case Qty
SPIN CLOSED						
638X208	½" F1807	½"	8"	B	100	100
638X212	½" F1807	½"	12"	B	100	100
638X312	¾" F1807	¾"	12"	B	50	50
638X208PK	½" F1807	½"	8"	C*	20	20
BRACKETED SPIN CLOSED						
638X212E	½" F1807	½"	12"	B	50	50
OPEN						
643X208	½" F1807	½"	8"	B	100	100
643X212	½" F1807	½"	12"	B	100	100



PowerPEX™

Stub Air™

Brazed Air Chamber Tee Fitting


- Eliminates on-the-job costs such as: measuring, cutting, cleaning, fluxing and soldering of up to four joints
- Sturdy brazed saddle joint cannot be damaged during field soldering and will not fracture due to jobsite abuse
- Provides stub out and air chamber with PEX connection in one piece



682XL5240



Models with open branches work great for tub valve connections, with only ONE solder joint needed.



Leakproof

Spin closed ends have **five** times the wall thickness of the copper tube. Each fitting is factory inspected.

Item No	Connection	Type	Branch		Air Chamber		Pkg	Min Qty	Case Qty
			CTS	Length	CTS	Length			
SPIN CLOSED									
682XL5240	½" F1807	L	½"	8"	½"	12"	B	25	25
682XL5240PK	½" F1807	L	½"	8"	½"	12"	C*	10	10
OPEN									
682XL5213	½" F1807	L	½"	1½"	½"	12"	B	25	25

