
WPS-78P

Weather Protection System
7/8” to Port Adaptor



General	Specification
Weight / Dimensions	.05 lbs | 24 g
Material	Silicone Rubber
Reusability	Unlimited


Compatible Port Dimensions



1 SURFACE SHOULD BE FREE OF FLATS, THREADS, OR RAISED LETTERING WHOSE CHARACTERS ARE TALLER THAN 1/8".

2 MINIMUM DISTANCE BETWEEN END OF THREADS AND ANY OBSTRUCTION

Compatible Port Dimensions



1 SURFACE SHOULD BE FREE OF FLATS, THREADS, OR RAISED LETTERING WHOSE CHARACTERS ARE TALLER THAN 1/8".

2 MINIMUM DISTANCE BETWEEN END OF NUT AND ANY OBSTRUCTION

Environmental	Specification	Comment
Installation Temperature Operating Temperature Storage Temperature	–40°C to +65°C –40°C to +65°C –55°C to +85°C	
Moisture Resistance	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
Corrosion Resistance	1000 Hours	ASTM B117
U.V. Resistance	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
H.A.L.T.	40 Hours	

www.jmawireless.com
+1 315-431-7100 | customerservice@jmawireless.com