

Paint Stop[™] Technology Ensures sharp, crisp lines

Light Tack - DELICATE SURFACES Painter's Tape • Ideal for Faux Finishes, Wallpaper and Fresh Paint • 60 Days Indoor Clean Removal

cantech)

VERY LIGHT ADHESION

LOW QUICK STICK

ion légère – Ruban pour peintres, SURFACES DÉLICATES ideal pour Faux-Finis, papier peints et peinture fraiche • Ideal pour Faux-Finis, papier peints et peinture fraiche S'enlève sans résidus, même après 60 jours en usage intérieur

Technologie Paint Stop Pour des démarcations et lignes précises

Paint

TOP

315 Series

EDG3 PRO + DELICATE MASKING TAPE

DESCRIPTION

The Edge Pro+ Delicate Masking tape provides a combination of special paper and adhesive. Its smooth, high quality Japanese washi paper assures less bleed-through and reduces the paint line demarcation. It's special adhesive provides a low initial tack yet will remain stuck to the surface and will peel cleanly without leaving residue. The Edge Pro+ Delicate is designed for masking delicate surfaces such as freshly cured paint, wallpaper and ceiling tiles. It's the tape of choice to use in for "Faux-Finish" projects.

APPLICATIONS

- The 315 masking tape provides a combination of premium orange washi paper coated with a specially formulated water based acrylic adhesive offering low adhesion level with a 60 day clean removal.
- Recommended for delicates surfaces, wallpaper, fresh cured painted surfaces and to create Faux-Finishes.

TECHNICAL DATA

Colour	Orange
Thickness	
Adhesion to steel	
Tensile strength	

STOCK SIZE

314-24 24 mm x 55 m — 36 rolls/case 314-36 36 mm x 55 m - 24 rolls/case 314-48 48 mm x 55 m - 24 rolls/case

The above specification represents average values. Actual production can vary. This selection and application of a tape is the responsibility of the buyer. Tape should be stored at room temperature and should not be exposed to sunlight. We reserve the right to make changes, without notice, to our products and specifications.

Please note:

The technical characteristics quoted are averages only and may vary within industry tolerances.

The final user must assure product suitability for the application and assumes all risks and liabilities.