



**T-521G**

Inline, Threaded Connection, 300 WOG, Class 150

| PART NUMBER | SIZE   | CASE | CARTON | WEIGHT |
|-------------|--------|------|--------|--------|
| 105-603G    | 1/2"   | 100  | 25     | 33     |
| 105-604G    | 3/4"   | 128  | 16     | 52     |
| 105-605G    | 1"     | 96   | 12     | 62     |
| 105-606G    | 1-1/4" | 36   | 9      | 39     |
| 105-607G    | 1-1/2" | 32   | 8      | 38     |
| 105-608G    | 2"     | 16   | 4      | 36     |

- Dezincification Resistant Brass Alloy
- Forged Lead Free Brass Body
- Can be Installed in Vertical or Horizontal Positions
- Bubble-Tight Teflon Seal
- IAPMO Certified - NSF 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



**S-521G**

Inline, Solder Connection, 300 WOG, Class 150

| PART NUMBER | SIZE   | CASE | CARTON | WEIGHT |
|-------------|--------|------|--------|--------|
| 105-613G    | 1/2"   | 100  | 25     | 33     |
| 105-614G    | 3/4"   | 128  | 16     | 54     |
| 105-615G    | 1"     | 96   | 12     | 60     |
| 105-616G    | 1-1/4" | 48   | 6      | 52     |
| 105-617G    | 1-1/2" | 32   | 4      | 40     |
| 105-618G    | 2"     | 16   | 2      | 42     |

- Dezincification Resistant Brass Alloy
- Forged Lead Free Brass Body
- Can be Installed in Vertical or Horizontal Positions
- Bubble-Tight Teflon Seal
- IAPMO Certified - NSF 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



**P-521G**

Inline, Press Connection, 300 WOG, Class 150

| PART NUMBER | SIZE   | CASE | CARTON | WEIGHT |
|-------------|--------|------|--------|--------|
| 105-623G    | 1/2"   | 120  | 20     | 35     |
| 105-624G    | 3/4"   | 96   | 8      | 42     |
| 105-625G    | 1"     | 68   | 17     | 36     |
| 105-626G    | 1-1/4" | 32   | 4      | 31     |
| 105-627G    | 1-1/2" | 24   | 3      | 38     |
| 105-628G    | 2"     | 18   | 3      | 40     |

- Dezincification Resistant Brass Alloy
- Forged Lead Free Brass Body
- Can be Installed in Vertical or Horizontal Positions
- Bubble-Tight Teflon Seal
- IAPMO Certified - NSF 61 & NSF 372
- ASME B16.51
- Wetted Surfaces Contain Less than .25% Lead Content



**E-521G**

Inline, Expansion Pex Connection, 300 WOG, Class 150

| PART NUMBER | SIZE | CASE | CARTON | WEIGHT |
|-------------|------|------|--------|--------|
| 105-633G    | 1/2" | 80   | 20     | 33     |
| 105-634G    | 3/4" | 80   | 20     | 33     |
| 105-635G    | 1"   | 72   | 18     | 33     |

- Dezincification Resistant Brass Alloy
- Forged Lead Free Brass Body
- Can be Installed in Vertical or Horizontal Positions
- Bubble-Tight Teflon Seal
- IAPMO Certified - NSF 61 & NSF 372
- ASTM F1960
- Wetted Surfaces Contain Less than .25% Lead Content

