

# Specifications



Photo is representative



## Eaton LE215AB04T

Eaton Cooper Power series loadbreak elbow, 200 A, Std V:15 kV, Max phase-to-ground:8.3 kV, AC 1 min:34 kV, DC 15 min:34 kV, Impulse:95 kV, Max corona:11 kV, Test:Yes, 0.61 inch, 0.97 inch, 15.5 mm, 24.6 mm, #2 AWG, #1 AWG, 20 pack

### General specifications

PRODUCT NAME	Eaton Cooper Power series loadbreak elbow
CATALOG NUMBER	LE215AB04T
UPC	194006008266
PRODUCT LENGTH/DEPTH	15.25 in
PRODUCT HEIGHT	18 in
PRODUCT WIDTH	15.25 in
PRODUCT WEIGHT	2.26 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE 386



Powering Business Worldwide

## Product specifications

TYPE	Loadbreak elbow
AC 1 MINUTE VOLTAGE WITHSTAND	34 kV
BASIC IMPULSE LEVEL	95 kV
CABLE INSULATION DIAMETER - MAX	0.97 in
CABLE INSULATION DIAMETER - MIN	0.61 in
SOLID OR COMPACT CONDUCTOR SIZE	#1 AWG
STRANDED OR COMPRESSED CONDUCTOR SIZE	#2 AWG
CURRENT RATING	200 A
DC 15 MINUTE WITHSTAND	34 kV
MAXIMUM RATING PHASE-TO-GROUND	8.3 kV
CORONA VOLTAGE LEVEL - MIN	11 kV
STANDARD PACK	20 pack
STANDARD VOLTAGE CLASS	15 kV

## Resources

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - LE215AB04T](#)

[Line installation and protective equipment specifiers guide](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

