



# Industrial remover

Industrial  
cleaning

## Remover for seals and adhesives

### 1. General description

---

Combination of powerful, non-chlorinated solvents created to easily remove seals, adhesives and putty. Protects the surfaces by eliminating the damage caused by excessive scratching.

### 2. Characteristics

---

- Increased penetration power.
- Controlled evaporation.
- Adheres well to vertical surfaces, ideal for fixed industrial equipment.
- Softens and facilitates the removing of conventional seals, cast joints and cement and putty seals.
- Removes carbonaceous deposits.
- Dissolves tars, greases, dry oils, adhesives, resinous deposits, etc.

### 3. Applications

---

Removes residues of seals and jointings on the top of the cylinder, gear box casings, speed-change gears, water pump flanges, etc. carbonaceous deposits on valve seats, cylinder tops, metallic components of the engine, etc., paints and coatings on metals, stones, hard surfaces; putty; glazing putty, sealing putty, adhesives.

text

### 4. Operating instructions

---

Cover painted surfaces before application. Wear safety goggles and gloves (resistant to chemical products, refer to the safety data sheet).

Stir properly before use and apply a thick film on the surface to be treated. Let the product do its work for 10 to 20 minutes. Remove the residues with a rag, a hard-bristle brush or a spatula.

Repeat the process if necessary.

Clean the treated surface with a degreasing solvent that is either an Industrial Degreasing Agent (ref. 6645) or Quick Drying Degreasing Agent (ref. 6641) to remove doughy or waxy residues.

Carry out a preliminary test on plastic materials and rubber.

Do not apply on live electrical devices.

Use only in properly ventilated areas.

***A material safety data sheet (MSDS) compliant to the EC regulation No. 1907/2006 Art.31 and amendments is available for all KF products.***



#### CRC Industries France SAS

12, Bld des Martyrs de Chateaubriant – Z.I. du Val d'Argent – B.P. 90028

F-95102 Argenteuil Cedex. - France

Tél.: + 33 (0)1 34 11 20 00 Fax.:+ 33 (0)1 34 11 09 96

S.A au capital de 1.936.667 € - R.C.S. Pontoise B 391 513 314 – APE 515 L

[www.crcind.com](http://www.crcind.com)





# Industrial remover

Industrial  
cleaning

## Remover for seals and adhesives

### 5. Typical characteristics of the product

---

Appearance	: Viscous liquid, opaque.
Density at 20 °C	: 0.92.
Distillation range of the solvents	: 40 to 200 °C.
Freezing point	: < - 20 °C.
Flash point (closed cup)	: < 0 °C.
pH	: neutral.
viscosity	: 700 to 1500 mPa.s.
Kauri-butanol value (of the solvents)	: > 120.
Vapour density (air = 1)	: > 2.
Solids content	: 1.5 % by weight.

### 6. Packagings

---

<b>Ref.: 6653</b> - Aerosol 650 ml gross - 500 ml net.	carton of 12 aerosols.
<b>Ref.: 6802</b> - 1 litre can	Single
<b>Ref.: 6654</b> - 5 litre bottle	Carton of 2 bottles

All the data in this publication is based on laboratory experiments and tests. In view of the wide variety of conditions and devices used, as well as the unforeseeable human factors that could have an important influence on the results of the application, we advice you to ensure the compatibility of the product before using it. All this information is given as objectively as possible, but without any guarantee, expressed or implied, on our part.

This data sheet can always, even at this moment, be revised for reasons related to the legislation, availability of components or to newly acquired knowledge. The latest version of this data sheet, which is the only one that is valid, shall be sent to you on request, or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register yourself on our website for this product, in order to receive every updated version of this document automatically.

Version: 6653 03 0212 05  
Date: 06 Aug 2013

