

**Specifications**

- Exceeds TIA 568.2-D component requirements
- Short links (less than 10M) supported
- Designed and tested for 1.5A of continuous current per pair

**Standards**

- TIA-568-C.2 Category 6A component
- IEC 60603-7-41 Category 6A component
- Qualified to 150% of IEEE 802.3bt current level
- IEC60512-99-002 for de-matting endurance under POE load
- IEEE 802.3an 10GBASE-T
- UL Plenum rated


**Performance**

ETL Quarterly Test Program assures Category 6A component compliance.



**Quick Lace Wire Manager**

Wire manager securely retains wires for either A or B wiring and is keyed to ensure correct polarity to jack body.



**COBRA-LOCK™ Termination**

Jack body terminates all wires at once and actively retains termination integrity.



**Easily Re-Terminate**

Release COBRA-LOCK™ with a small screwdriver and reuse wire manager up to 25 times.

**NEXTSPEED® Ascent Category 6A Jacks with COBRA-LOCK™ Termination**

Color	Single Pack	24-Pack
Black	HJU6ABK	HJU6ABK24
Blue	HJU6AB	HJU6AB24
Brown	HJU6ABN	HJU6ABN24
Gold	HJU6AGL	HJU6AGL24
Gray	HJU6AGY	HJU6AGY24
Green	HJU6AGN	HJU6AGN24
Ivory	HJU6AEI	HJU6AEI24
Office White	HJU6AOW	HJU6AOW24
Orange	HJU6AOR	HJU6AOR24
Pink	HJU6APK	HJU6APK24
Purple	HJU6AP	HJU6AP24
Red	HJU6AR	HJU6AR24
White	HJU6AW	HJU6AW24
Yellow	HJU6AY	HJU6AY24

See color chart on page B2