



Pass and Seymour  
20A/30A 4-Wire and 5-Wire Right Angle Adapter  
Part No. L203045AN



ANGLE ADAPTER 20/30A 4and5W TURNLOCK

## Features & Benefits

Angle plugs and adapters both allow for 4-position face rotation.

Angle adapters (sold separately) will accommodate all P&S Turnlok style plugs and connectors on a retrofit basis. Simply remove the straight handle body from the plug or connector face assembly, and replace with the angle adapter.

Angle plugs and adapters have the same wide cord diameter range (.230" - 1.150") that is present on all Turnlok plugs and connectors.

20/30A 3 Wire Turnlok: Right Angle Adapters are adjustable up to 8 positions.

Tri-drive assembly and cord-grip screws are standard on all angle plugs and adapters.

## Specifications

### General Info

|                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| Product Line       | Pass & Seymour | Color             | Black  |
| UPC Number         | 785007165456   | Country Of Origin | Mexico |
| Application Sector | Industrial     | Standard          | UL498  |

### Dimensions

|                   |          |                  |         |
|-------------------|----------|------------------|---------|
| Product Width US  | 2.675 in | Product Depth US | 1.65 in |
| Product Height US | 3.868 in |                  |         |

### Listing Agencies / 3rd Party Agencies

|                     |        |              |     |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 146159 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

---

Technical Information

|                          |                                                                                                       |           |            |
|--------------------------|-------------------------------------------------------------------------------------------------------|-----------|------------|
| Number of Wires          | 4                                                                                                     | Amperage  | 20 A       |
| Number of Poles          | Double Pole                                                                                           | Wire Size | 18 - 8 AWG |
| Environmental Conditions | Flammability: UL94 V2: Operating Temperature: Maximum continuous +115°C, minimum -40°C without impact |           |            |

---