


		B-Twist™ WIRE CONNECTOR		MODEL BT2	
FEATURES/BENEFITS:					
		- CONNECTION COMES TO TORQUE QUICKLY TO GET THE JOB DONE EFFECIENTLY - ROUNDED DIAL-TOP PROVIDES FAST, FINGERTIP START - LONG, SWEPT WINGS OFFER HIGH TORQUE IN A LOW-PROFILE DESIGN - WIDE, EXPANDING SPRING MAKES FOR EASY STARTS ON EVEN THE LARGEST COMBINATIONS - WIDE RANGE COVERS FROM 2 #18 TO 2 #8			
ELECTRICAL:					
VOLTAGE:					
GENERAL:		600 V MAX			
SIGN/LUMINAIRES:		1000 V MAX			
PHYSICAL:			STANDARDS & SPECIFICATIONS:		
HOUSING: GRAY THERMOPLASTIC POLYESTER			UL 486 C		
INSERT: STEEL			UL 94V-2 FLAME RATING		
PLATING: ZINC			CSA- C22.2 NO. 188		
TEMPERATURE: 105° C (221° F)			RoHS COMPLIANT		
			IEC 998-2-4		
					
WIRE RANGE & COMBINATIONS:			- Solid and/or stranded wire combinations unless stated otherwise - Consult website for other combinations not listed		
BT2 (RED)					
STRIP LENGTH: 1/2"					
4 to 6 #22					
3 to 6 #20					
2 to 6 #18					
1 to 6 #16					
1 to 6 #14					
1 to 5 #12					
1 to 4 #10					
2 #10 w/ 2 #12 w/ 1 #14					
3 #12 w/ 2 #14 w/ 1 #16					
5 #20 w/ 1 #22					
DIMENSIONS:					
					
ORDERING INFO:					
MODEL	COLOR	QUANTITY	CAT. NO.	WEIGHT (lbs)	
BT2	RED	BOX OF 100	BT2-1	0.69	
		JAR OF 500	BT2-500JR	3.75	
		BARREL OF 25,000	BT2-SK	167.50	
FACTORY CONTACT:			SALES CONTACT:		
IDEAL INDUSTRIES, INC. 1375 PARK AVENUE, SYCAMORE, IL, 60178 P: (800) 324-9571 F: (888) 222-6140 E: oem@idealindustries.com					