

MEDIUM GRADE FILAMENT TAPE



STRENGTH

HIGH TACK

DESCRIPTION

A strong filament tape consisting of glass filaments laminated to polypropylene film and coated with an aggressive high tack adhesive. It is water and moisture resistant.

MAIN FEATURES

- Strength.
- Water resistant.
- High tack.
- Excellent shear value.
- Little stretch.

APPLICATIONS

- To hold pharmacy cabinet frame together.
- For reinforcing baker's trays.
- As a bond breaker in the concrete industry.
- Palletizing of boxes.
- Strapping rods, moulding, tubes plywood without danger of scratching, staining or damaging.
- Reinforcing boxes, protecting contents from pilferage.

TECHNICAL DATA

Color.....	Ivory
Backing.....	Polypropylene film laminated to fiberglass filament
Adhesive.....	Synthetic rubber/resin
Thickness.....	5.0 mil
Adhesion to steel.....	80 oz/in
Tensile strength.....	110 lb/in
Elongation.....	3.5%
Temperature Resistance.....	0°C to 60°C (32°F to 140°F)

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.