

# Portland



## Colors



White  
VTL PLWH



Beige  
VTL PLBE



Light Gray  
VTL PLLG




Gray  
VTL PLGR



Dark Gray  
VTL PLDG

## Sizes



24" x 24" x 9mm Rectified



12" x 24" x 9mm Rectified

# PORTLAND

## Field Tiles\*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 24" Rectified	23.63" x 23.63"	9.00mm	Matte/Natural
12" x 24" Rectified	11.81" x 23.62"	9.00mm	Matte/Natural
* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.			

## Coordinating Trims\*

SIZE	ACTUAL	FINISH
3" x 24" Bullnose	2.81" x 23.63"	Matte/Natural
Recommended Grout Joint: 1/8" - Rectified 3/16" - Non Rectified		

## Product Characteristics

	MATTE/NATURAL
Breaking Strength (ASTM C648 or ISO 10545-4)	≥ 1300 N
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	> 0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	≤ 145 mm3
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	≤ 0.1%
Certifications	LEED Certified
Country of Origin	Italy
Shade Variation Code	V2

## Application\*\*

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	•

\*\* These recommendations are not defined by ANSI Standards

## Material

Porcelain



Made in Italy



Import



V2 Slight Variation



DCOF: >0.42



LEED Certified



Scan QR Code for  
Product Information and  
Installation Images

# Request samples.

www.vitlsurfaces.com  
samples@vitlsurfaces.com



VITL  
COMMERCIAL SURFACES