

# MARBLE OBSESSION™

COLORBODY™ AND GLAZED PORCELAIN FLOOR,  
GLAZED CERAMIC WALL & MOSAICS

**MARAZZI**®

DARE TO BE BOLD™

MARBLE LOOK



# MARBLE OBSESSION™

The pursuit of classic beauty and luxury is found within Marble Obsession™, a collection inspired by an array of three unique marble visuals. Its alluring color palette ranges from a classic white with dramatic gold veining to an attractive with grey featuring white striations. This well-rounded series offers versatility through a mix of different shapes, sizes, and finishes. Transcend traditional marble installations and step into the next level of marble-inspired designs with a 2x5 Picket mosaic, 8" Hex, and a 6" Arabesque wall piece, designed to mesmerize and satisfy your desire for modern elegance.



COVER PHOTO: GRIGIO  
ABOVE PHOTO: CALACATTA GOLD

MARBLE LOOK

# MARBLE OBSESSION™

COLORBODY™ AND GLAZED PORCELAIN FLOOR, GLAZED CERAMIC WALL & MOSAICS

# MARAZZI®

DARE TO BE BOLD™

FINISHES: MATTE | POLISHED | SATIN

### USAGE



### MATERIAL



### PRICING



### SPECIAL FEATURES



MARBLE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

## COLORBODY™ PORCELAIN FLOOR TILE - MATTE & POLISHED



**MB20** Arabescato



**MB21** Calacatta Gold



**MB22** Grigio

## GLAZED PORCELAIN 8" HEXAGON FLOOR TILE - MATTE



**MB20** Arabescato

**MB21** Calacatta Gold

**MB22** Grigio

## GLAZED CERAMIC 6" ARABESQUE WALL TILE - MATTE



**MB20** Arabescato

**MB21** Calacatta Gold

**MB22** Grigio

## GLAZED CERAMIC 2" x 5" PICKET MOSAIC - SATIN



**MB20** Arabescato

**MB21** Calacatta Gold

**MB22** Grigio

## GLAZED CERAMIC 2" x 2" MOSAIC - MATTE



**MB20** Arabescato

**MB21** Calacatta Gold

**MB22** Grigio



VISIT [MARAZZITILE.COM/WHYTILE](http://MARAZZITILE.COM/WHYTILE) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS. \* Applicable to porcelain tile only.

FINISHES: MATTE | POLISHED | SATIN

<b>USAGE</b>	<b>MATERIAL</b>	<b>PRICING</b>	<b>SPECIAL FEATURES</b>
FLOOR WALL COUNTERTOP SHOWER FLOOR EXTERIOR FLOOR	PC CG PG	LOW HIGH	STEPWISE TRUEEDGE MADE IN THE U.S.A. LARGE FORMAT MOSAIC/DECO ENCAUSTIC TERRAZZO PAVER CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

MARBLE LOOK

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 24 Floor Tile*	23-7/16" x 23-7/16" (59.44 cm x 59.44 cm)	5/16"	15.20	4
	12 x 24 Floor Tile*	11-5/8" x 23-7/16" (29.56 cm x 59.44 cm)	5/16"	16.83	9
	8" Hexagon Floor Tile*	7-7/8" x 9-1/8" (20.04 cm x 23.16 cm)	5/16"	9.37	25
	6" Arabesque Wall Tile*	5-1/4" x 6" (13.33 cm x 15.24 cm)	5/16"	10.80	90
	2" x 5" Picket Mosaic (Dot-mounted)*	12-1/4" x 11-1/8" Sheet (31.12 cm x 28.26 cm Sheet)	1/4"	8.76	12
	2" x 2" Mosaic (Dot-mounted)*	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	1/4"	10.00	10

- \* Available in Matte & Polished finishes.
- ♦ Available in Matte finish only.
- \* Available in Satin finish only.

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■*
Wet & Level - Interior Floor	≥ 0.42	■**
Shower Floors (Residential or Light Commercial)	≥ 0.42	■*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■*
Pool Linings	N/A	■**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [marazzitile.com/DCOF](http://marazzitile.com/DCOF).

### APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall and mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

- \* Floor and Mosaic tile only.
- \* Matte only.
- ♦ 2 x 2 Mosaic tile only.
- \*\* Mosaic tile only.

## PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs	> 120 - 230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0 (Matte) 6.0 (Polished)	4.0 - 6.0	8.0 (2 x 2 Matte Mosaic) 6.0 (2 x 5 Satin Picket)
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: [marazzitile.com/information/TestResults](http://marazzitile.com/information/TestResults).

## TRIM

Description	Number	Size	Shape
Floor Bullnose*	P43F9	3 x 24	
Jolly**	S1/212J	1/2 x 12	

- \* Available in Matte & Polished.
- \*\* 4 pieces per card. 6 cards per carton.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
<p><b>Floor:</b> 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)</p> <p><b>Wall:</b> 1/16"</p> <p><b>Mosaic:</b> 1/8"</p>	

## DURABILITY

### Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazzitile.com/Factors](http://marazzitile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [marazzitile.com/LargeTiles](http://marazzitile.com/LargeTiles) for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values <0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at [www.tileusa.com](http://www.tileusa.com).

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

## FEATURES

	POST-CONSUMER RECYCLED MATERIALS		PRE-CONSUMER RECYCLED MATERIALS
	MADE IN THE U.S.A.		REVEAL IMAGING®
	CERTIFIED PORCELAIN™		ZEROTOX

All or select items within this series meet the requirements for these qualifications. For more information visit [marazzitile.com](http://marazzitile.com).