


Organic Roots



Colors




White
VTL OTWH




Ivory
VTL OTIV



Taupe
VTL OTTP



Green
VTL OTGN



Blue
VTL OTBU




Brown
VTL OTBW



Light Gray
VTL OTLG



Medium Gray
VTL OTMG




Black
VTL OTBK

Sizes



24" x 48" x 9mm Rectified



12" x 24" x 9mm



3" x 12" x 9mm

ORGANIC ROOTS

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 48" Rectified	23.63" x 47.25"	9.00mm	Matte/Natural
12" x 24"	11.75" x 23.63"	9.00mm	Matte/Natural
3" x 12"	2.75" x 11.75"	9.00mm	Matte/Natural
* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.			

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
12" x 12" Origin Mosaic	11.75" x 11.75"	Matte/Natural
2" x 2" Mosaic	11.75" x 11.75"	Matte/Natural
3" x 24" Bullnose	2.88" x 23.63"	Matte/Natural
6" x 12" Cove Base	5.88" x 11.75"	Matte/Natural
Recommended Grout Joint: 1/8" - Rectified 3/16" - Non Rectified		

Product Characteristics

MATTE/NATURAL	
Breaking Strength (ASTM C648 or ISO 10545-4)	≥ 350 lbf
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	> 0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	≤ 0.5%
Certifications	HPD EPD Greenguard VOC Free
Country of Origin	USA
Shade Variation Code	V2

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

Material

Color-Body Porcelain



Made in USA



Ready Ship



V2 Slight Variation



DCOF: >0.42



HPD, EPD, Greenguard, VOC Free



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
SURFACES
COMMERCIAL