



PDU15B2F8R BASIC PDU



Engineered to distribute UPS, generator or utility AC power to equipment.

The CyberPower PDU15B2F8R, a ten-outlet (two front, eight rear) rackmount basic power distribution unit (PDU), provides 120V 15A output. It distributes power to ten NEMA 5-15R receptacles from a single NEMA 5-15P plug with unfiltered electrical pass-through. Designed for datacenters and other electrically demanding applications, the PDU15B2F8R has rugged, industrial-grade metal housing and a 15-foot AC power cord. It can be mounted either horizontally or vertically, includes a cord retention tray, and is ETL/RoHS certified. A limited lifetime warranty covers defects in materials and workmanship in the product under normal use and conditions.

TYPICAL APPLICATIONS

- VoIP Phone Systems
- Network Closets
- Data Centers
- Industrial Environments

FEATURES

- Phase: Single
- Amps: 15A (Derated to 12A)
- Volts: 100 - 125 V
- Frequency: 50Hz/60Hz
- Plug type: NEMA 5-15P
- Outlets: 10 x NEMA 5-15R
- Outlet location: 2 Front / 8 Rear
- Size: 1U Rackmount
- Dimensions (in.): 17.5W x 1.75H x 2.25D
- Cord length (ft.): 15
- Warranty: Limited Lifetime

SPECIFICATIONS

INPUT	
Cord Length (ft.)	15 ft (4.6 m)
Derated Input Current	12 A
Input Frequency Range	50Hz - 60Hz
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Straight

OUTPUT	
Nominal Output Voltage	100 - 125 VAC
Outlet Type	10 x NEMA 5-15R
Outlets - Front	2
Outlets - Rear	8
Outlets - Total	10
Overload Protection	15 A

PDU15B2F8R

BASIC PDU



SPECIFICATIONS

PHYSICAL	
Adjustable Mounting Brackets	2 sets (L-Short, L-Long)
Color	Black
Cord Retention Tray/ Cord Organizers	Yes
External Site Ground Pin	Yes
Form Factors Supported	1U Rackmount OU Vertical Rackmount Undercounter Installation Supported
Material of Construction	Metal
Rack Height	1U
Style	Rackmount Vertical Rackmount Under-Counter

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	44.45 x 4.45 x 5.72 cm
Physical Dimensions - Width/Height/Depth (mm)	445 x 44 x 57 mm
Physical Dimensions - Width/Height/Depth (in.)	17.5 x 1.75 x 2.25 in.
Weight (kg)	1.81 kg
Weight (lbs.)	4.0 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	17.83 x 6.68 x 51.13 cm
Shipping Dimensions - Width/Height/Depth (mm)	178.31 x 66.8 x 511.3 mm
Shipping Dimensions - Width/Height/Depth (in.)	7.02 x 2.63 x 20.13 in.
Shipping Weight (kg)	9.47 kg
Shipping Weight (lbs.)	20.88 lbs.

ENVIRONMENTAL	
Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Operating Relative Humidity	0 - 95% (non-condensing)
Operating Temperature	32 - 95 °F (0 - 35 °C)
Storage Elevation	0 - 50,000 ft (0 - 15,239 m)
Storage Temperature	5 - 113 °F (-15 - 45 °C)

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL62368 UL60950-1

WARRANTY	
Product Warranty	Limited Lifetime Warranty