

► **Code Number**

3913264

► **Description**

Concealed Urinal Flushometer, for 3/4" back spud urinals.

► **Flush Cycle**

0.5 gpf/1.9 Lpf

► **Specifications**

Quiet, Concealed, Diaphragm Type, Rough Brass Urinal Flushometer for either left or right hand supply with the following features:

- Dual Filtered Fixed Bypass Diaphragm
- Vacuum Breaker
- Spud Coupling for 3/4" Concealed Back Spud Urinals
- Chrome Plated Exposed Flushometer Parts
- Elbow Flush Connection
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Diaphragm, Handle Packing and Vacuum Breaker to be molded from PERMEX® Rubber Compound for Chloramine Resistance
- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- Flush accuracy controlled by CID® technology

Valve Body, Cover, Tailpiece and Control Stop will be in conformance with ASTM Alloy Classification for Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

- 3/4" I.P.S. Wheel Handle Bak-Chek® Angle Stop

► **L Dimension**

Specify the "L" Dimension for the proper length of the Handle Assembly and Flush Connection. The "L" Dimension is equal to the Wall Thickness (to the nearest whole inch) plus 2 3/4" (70 mm).

► **Variations**

12 3/4 LDIM

► **Accessories (Sold Separately)**


See Accessories Section of the Sloan catalog for available accessories

► **Fixtures**

Consult factory for matching Sloan brand fixture options.



Model Royal 195 w/ Handle Shown



Model Royal 195 w/ Handle Shown

► **Compliance & Certifications**



This space for Architect/Engineer Approval