

PREPACKAGED AND JOB READY SYSTEMS

ACCESSORIES FOR FIELD-ASSEMBLED SYSTEMS

FLEX-HOSE DISCHARGE ASM.
 P/N 10-2038 with 30" (76 cm) hose

Z-RAIL® DISCONNECT SYSTEM

- P/N 39-0137 1-1/4" (3.2 cm) H x 1-1/4" (3.2 cm) V ductile Iron
- P/N 39-0138 1-1/4" (3.2 cm) H x 1-1/4" (3.2 cm) V with stainless steel upper bracket
- P/N 39-0139 Intermediate bracket stainless steel

STAINLESS STEEL LIFTING CABLES AND ROD

- P/N 39-0031 8' (2.4 m) cable
- P/N 39-0032 12' (3.7 m) cable
- P/N 39-0069 1' (0.3 m) rod
- P/N 10-0789 stainless steel lifting bail

PREWIRED CONDUIT

(10-0580 Qwik Box Required)

- P/N 5100-0016 - 25' (8 m)
- P/N 5100-0017 - 35' (11 m)
- P/N 5100-0018 - 50' (15 m)

GALVANIZED 1.25" DISCH. ELBOW
 P/N 018386

CHECK VALVE

- P/N 30-0223 1.25" NPT brass

BALL VALVE

- P/N 30-0165 1.25" PVC
- P/N 30-0213 1.25" NPT brass

FIELD-MOUNT SYSTEMS

SIMPLEX	
REQ.	REQ.
1 810 or 815 grinder	P/N ____ (A)
1 control panel/alarm system	P/N ____ (B)
1 piggyback pump switch	P/N ____ (C)
1 control switch (if required)	P/N ____ (C)
1 weight for alarm float (if required)	P/N ____ (D)
1 junction box (Optional)	P/N ____ (F)
1 optional accessories	P/N ____ (F)
	P/N ____ (F)
	P/N ____ (F)
	P/N ____ (F)

OUTDOOR	
REQ.	REQ.
1 810 or 815 grinder	P/N ____ (A)
1 control panel/alarm system	P/N ____ (B)
1 piggyback pump switch	P/N ____ (C)
1 control switch (if required)	P/N ____ (C)
1 junction box (if required)	P/N ____ (D)
1 basin, cover and hardware	P/N ____ (F)

INDOOR	
REQ.	REQ.
1 810 or 815 grinder	P/N ____ (A)
1 alarm panel	P/N ____ (B)
1 piggyback pump switch	P/N ____ (C)
1 weight for alarm float	P/N ____ (C)
1 basin, cover and hardware	P/N ____ (F)