

Windsor Place

SANDSTONE LOOKS ARE MATCHED WITH BUILT-IN ANTIMICROBIAL PROTECTION THAT PREVENTS THE GROWTH OF BACTERIA.

Colors



Ash Grey



Charcoal



Dove




Lace



Mocha




Pearl




Tan

Sizes



47" x 47"
Rectified



27" x 47"
Rectified



24" x 24"
Rectified



18" x 35"
Rectified



12" x 24"
Rectified

Field Tiles*

SIZE	THICKNESS	FINISH
12" x 24" Rectified	9.5 mm	Bush Hammered, Matte & Polished
12" x 24" Mural Decorative Rectified	9.5 mm	Matte
18" x 35" Rectified	9.5 mm & 20 mm	Matte
24" x 24" Rectified	9.5 mm	Matte
24" x 47" Rectified	9.5 mm	Bush Hammered, Matte, Matte w/ Shield & Polished
24" x 47" Mural Decorative Rectified	9.5 mm	Matte & Matte w/ Shield
47" x 47" Rectified	9.5 mm	Matte

Mosaics & Coordinating Trims*

SIZE	THICKNESS	FINISH
13" x 47" Left Corner Rectified	9.5 mm	Matte
13" x 47" Right Corner Rectified	9.5 mm	Matte
13" x 47" Stair Tread Rectified	9.5 mm	Bush Hammered & Matte
13" x 47" Step Rectified	9.5 mm	Matte
2" x 2" Mosaic	9.5 mm	Matte
2" x 35" Bullnose Rectified	9.5 mm	Matte
3" x 24" Bullnose Rectified	9.5 mm	Matte

Product Characteristics

Breaking Strength (ASTM C648 or ISO 10545-4)	Range of ≥ 12000 N to ≥ 2000 N
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	Range of ≥ 0.65 to ≥ 0.50
Deep Scratch Resistance - Unglazed (ISO 10545-6)	Not Resistant
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	Not Applicable
Water Absorption (ASTM C373 or ISO 10545-3)	$\leq 0.5\%$
Certifications	Greenguard
Country of Origin	Italy
Shade Variation Code	v3

*Not all sizes/trims are available in all colors and finishes

WITH BUILT-IN ANTIMICROBIAL PROTECTION THAT PREVENTS THE GROWTH OF BACTERIA, THIS COLLECTION IS PERFECT FOR MINIMALIST APPLICATIONS OR ENVIRONMENTS THAT CAN BENEFIT FROM AN EXPANSE OF NATURE-INSPIRED STONE.

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com

