

MOBILE LED PROJECTOR ML750



PALM-SIZED PROJECTION POWERHOUSE



- Incredibly light and small. Unbelievably powerful and bright
- PC Free presentations with built-in Office Viewer Powerful LED light source
- Present directly from your mobile device – HDMI/MHL connectivity
- Wireless presentation capability via optional adapter
- Powerful LED light source means no lamps to replace



Present your best wherever you go with the ultra-compact Optoma ML750 portable LED projector. The power and performance of a full sized projector on the palm of your hand.

Delivering an impressive 700 ANSI lumens and 10,000:1 contrast ratio, with razor sharp focus and magnificent color accuracy. The Optoma ML750 will make your presentations more impactful than ever before.

Designed for traveling professionals, the palm-sized Optoma ML750 weighs less than one pound. Has built-in Media player and Office Viewer for completely PC-Free presentations. HDMI and MHL connectivity for direct from mobile device presentations. Its LED light source is rated to last over 20,000 hours so you can present with confidence. Never a bulb to buy or replace.

CONNECTIVITY (May require optional accessories)



COMPUTERS



SMART PHONES



TABLETS



BLU-RAY/DVD PLAYERS



SET TOP BOXES



CAMCORDERS



GAME CONSOLES



DIGITAL CAMERAS



Apple TV®



Roku®



USB



microSD

MOBILE LED PROJECTOR — ML750

OPTICAL/TECHNICAL SPECIFICATIONS

Display Technology	Single 0.45" DMD DLP® Technology by Texas Instruments™
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	VGA: WSXGA+ (1680 x 1050) HDMI: HD 1920 x 1080
Brightness	700 Lumens
Contrast Ratio	10,000:1 (full on/full off)
Displayable Colors	16.7 Million
Light Source Life and Type	20,000+ hours LED
Projection Method	Front, rear, ceiling mount, table top
Keystone Correction	±40° Vertical, auto keystone correction
Uniformity	>85%
Offset	100%
Aspect Ratio	16:10 Native, 16:9 and 4:3 compatible
Throw Ratio (distance/Width)	1.5 (distance/width)
Projection Distance	1.8'–10.6' (0.55–3.23 m)
Image Size (Diagonal)	17"–100" (0.43–2.54 m)
Projection Lens	F=2.0, f=14.95 mm
Digital Zoom	1.7x
Audio	One 1-Watt speaker
Noise Level (Normal/Bright)	30dB
Remote Control	IR remote control
Operating Temperature	41–104°F (5–40°C), 85% max humidity
Power Supply	AC Input 100–240V, 50–60Hz, auto-switching DC output: 19v/3.2A, 65W
Power Consumption	Max 62W, <0.5W (standby)
Memory	1.5GB Onboard memory, microSD slot supports up to 32GB

COMPATIBILITY SPECIFICATIONS

Computer Compatibility	WSXGA+, SXGA+, WXGA+, WXGA, SXGA, XGA, SVGA, VGA resized, VESA, PC and Macintosh compatible
Video Input Compatibility	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)
3D Compatibility*	120Hz frame sequential 3D for resolutions up to XGA, 60Hz field sequential 3D for resolutions up to 480i. Not compatible with 3DXL.
Vertical Scan Rate	50–120Hz
Horizontal Scan Rate	15–100kHz
User Controls	Complete on-screen menu, adjustments in 16 languages
Image file compatibility	.jpg, .bmp
Office file compatibility	PowerPoint, Word, Excel, .pdf
Music file compatibility	.mp3, .wma, .ogg, .adpcm-wav, .pcm-wav, .aac
Video file compatibility	.avi, .mkv, .divx, .ts, .dat, .vob, .mpg, .mpeg, .mov, .mp4, .rm, .rmvb, .wmv
I/O Connection Ports	24-pin universal port (VGA), HDMI, microSD, USB-A

PHYSICAL SPECIFICATIONS

Security	Kensington® Lock Port
Weight	Projector: 14.1 oz Power adaptor: 5.1 oz
Dimensions (W x H x D)	4.1" x 1.5" x 4.2" (104 x 38 x 107 mm)



Warranty

1 Year limited parts and labor warranty on the projector, 1-year or 20,000 hour light source warranty (whichever comes first)

In the Box (Standard Accessories)

ML750, I/O cable (VGA & composite input), carrying case, AC power cable, power adapter, remote control, batteries, quick start user manual

Accessories

Wi-Fi adapter: WUSB
Remote (replacement): BR-ML75N
AC power adapter (replacement): BC-ML55PDX
AC power cord (replacement): BC-PUPNXY02
Universal to VGA/audio cable (replacement): BC-PK5AVGX
Carrying case (replacement): BK-ML70S

UPC 796435 41 903 5

www.OptomaUSA.com

Optoma
Projector Expert

*3D content can be viewed with DLP Link active shutter glasses when the projector is receiving a compatible 3D signal from a compatible source device. Please visit www.OptomaUSA.com for more information.

Copyright © 2013 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 05272020