



# PDU13104 | BASIC PDU SERIES



Deliver reliable power to electronic equipment, servers, and network/telecom devices

Deliver reliable unfiltered power to connected equipment with the CyberPower PDU13104 basic 3-Phase PDU. Designed for data centers and other electrically demanding applications, this unit features rugged, industrial-grade metal housing, network-grade outlets and operates in high temperatures up to 140°F (60°C).

The PDU13104 supports a 200V-240V 50A input, includes 36 IEC outlets, and provides a maximum output load of 14.5kW. The CyberPower PDU13104 is protected by a three-year limited warranty.

### TYPICAL APPLICATIONS

- Data Centers
- Corporate Servers
- Network Closets

### FEATURES

- Phase: 3-Phase
- Amps: 50 A (Derated to 35 A)
- Volts: 200 V - 240 V
- Max. Output Load: 14.5 kW
- Frequency: 50/60 Hz
- Input Plug Type: Hubbell CS8365C
- Outlets: 30 x IEC-320 C13 + 6 x IEC-320 C19
- Size: 0U Rackmount
- Cord Length (ft): 10
- Dimensions (in): 2.2W x 70.5H x 2.2D
- Warranty: Three-Year

## SPECIFICATIONS

INPUT	
Cord Length	10 ft (3.0 m)
Derated Input Current	35 A
Input Frequency Range	50 Hz - 60 Hz
Input Plug Type	Hubbell CS8365C
Maximum Input Current	50 A
Nominal Input Voltage	200 - 240 VAC
Phase	3-Phase

OUTPUT	
Nominal Output Voltage	200 - 240 VAC
Outlet Type	30 x IEC-320 C13 6 x IEC-320 C19
Outlets - Number of Banks	3
Outlets - Total	36
Overload Protection	20 A x 3

# PDU13104

## BASIC PDU SERIES

### SPECIFICATIONS CONT.

PHYSICAL	
Adjustable Mounting Brackets	1 Set
Color	Black
Cord Retention Tray/ Cord Organizers	Yes
Form Factors Supported	OU Vertical Rackmount
Material of Construction	Metal
Rack Height	OU

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	5.59 x 179.07 x 5.59 cm
Physical Dimensions - Width/Height/Depth (mm)	56 x 1791 x 56 mm
Physical Dimensions - Width/Height/Depth (in.)	2.2 x 70.5 x 2.2 in.
Weight (kg)	6.3 kg
Weight (lbs.)	13.9 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	21.59 x 16.0 x 203.45 cm
Shipping Dimensions - Width/Height/Depth (mm)	215.9 x 160.02 x 2034.54 mm
Shipping Dimensions - Width/Height/Depth (in.)	8.5 x 6.3 x 80.1 in.
Shipping Weight (kg)	9.71 kg
Shipping Weight (lbs.)	21.4 lbs.

ENVIRONMENTAL	
Operating Elevation	0 - 11,480 ft (0 - 3,499 m)
Operating Relative Humidity	0 - 95 % (non-condensing)
Operating Temperature	23 - 140 °F (-5 - 60 °C)

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL 60950-1 FCC Class A

WARRANTY	
Product Warranty	Three-Year Limited