





SPL3 LCR SOUNDBAR DATA SHEET

TECHNICAL SPECIFICATIONS

UOM	SPL3 LCR Each
Tweeter	(3) 1" (25mm) Neodymium Soft Dome
Woofer	(4-6) 3.5" (89mm) High Excursion
Frequency Response	80Hz-22 kHz +/-3dB
Impedance	4/8 ohms/Channel (Config. dependent)
Recommended Power Range	5 watts minimum; 100 watts maximum
Sensitivity (2.83V/1m)	86dB SPL
Enclosure	Aircraft Grade Aluminum
Width (W)	Built-to-Order 37" (940mm) minimum
Dims (Depth x H)	1.58" x 4" (40mm x 101mm)



FEATURES

- Paintable grille available by request only
- LCR format of this bar features left, right, and center channels
- Through-hole mount, TV mount, or wall mount options, mounting brackets sold separately
- Available in standard or marine grade

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2025 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.

JAMES by SONANCE • 2185 Park Place • Minden, NV 89423 • USA • PHONE: (775) 461-7500 • www.sonance.com

11.11.2025