

Eaton LEJ215DD00T

Catalog Number: LEJ215DD00T

Eaton Cooper Power series loadbreak elbow, Std V:15 kV, Max phase-to-ground:8.3 kV, AC 1 min:DC 15 min:34 kV, DC 15 min:53 kV, Impulse:95 kV, Max corona:11 kV, Test:Yes, 0.89 inch, 1.22 inch, 22.6 mm, 30.0 mm, 20 pack, Jacket seal:Yes

General specifications



Product Name	Catalog Number
Eaton Cooper Power series loadbreak elbow	LEJ215DD00T
	UPC
	194006014397
Product Length/Depth	Product Height
15.25 in	18 in
Product Width	Product Weight
15.25 in	3.527 lb
Compliances	Certifications
Not Applicable	IEEE 386

defaultTaxonomyAttributeLabel

Type

Loadbreak elbow

AC 1 minute voltage withstand

34 kV

Basic impulse level

95 kV

Cable insulation diameter - max

1.22 in

Cable insulation diameter - min

0.89 in

Stranded or compressed conductor size

No connector

Current rating

200 A

DC 15 minute withstand

53 kV

Maximum rating phase-to-ground

8.3 kV

Corona voltage level - min

11 kV

Standard pack

20 pack

Standard voltage class

15 kV

Features

Flex Center

Resources

Specifications and datasheets

[Eaton Specification Sheet - LEJ215DD00T](#)

[Line installation and protective equipment specifiers guide](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia