

Edge Uniboot Jumper Standard LC Uniboot MM / Standard LC Uniboot MM, OM4 50um, 2F, DFX 250 Riser, Standard Aqua Jacket 5 Meters

CORNING

Part Number:
797902QD120005M

EDGE™ Reverse Polarity Uniboot Duplex Jumpers allow for the quick and easy conversion from a TIA-568 A-B polarity to a TIA-568 A-A polarity without exposing the fibers or needing any tools. This jumper comes with a straight-through polarity from the factory, but you can convert it to a flipped jumper. This uniboot design allows one cable to carry both fibers, reducing the jumper bulk when routing.

This product is available for Quick Connect 48 hour shipping. Learn more here:

[Quick Connect Program](#)

Features and Benefits

State-of-the-art manufacturing processes

Advanced technology results in unsurpassed product consistency and quality

Global operations


Mitigates trade barriers or supply disruptions

Flexible design options

Choice of materials for strength elements and fiber properties for various application requirements

Superior performance testing

Each termination is tested to ensure the highest network performance



Edge Uniboot Jumper Standard LC Uniboot MM / Standard LC Uniboot MM, OM4 50um, 2F, DFX 250 Riser, Standard Aqua Jacket 5 Meters



Specifications

General Specifications	
Flame Rating	Riser (OFNR)
Fiber Category	50 µm MM (OM4)
Cable Assembly Type	Two Fiber
Application	Data Center, General Building Applications, Vertical Riser
Cable Type	Interconnect

Standards	
Fiber Standards	TIA/EIA-492AAAC-A, Tested with minEMBc method to TIA/EIA-455-220, IEC 60793-2-10 Type A1a.2 Ed.2.0, IEC 60793-1-49 Ed.2.0, ITU-T G.651, ISO/IEC 11801 Ed.2.2 Cat. OM3

Standards	
Fiber Standards	TIA/EIA-492AAAC-A, Tested with minEMBc method to TIA/EIA-455-220, IEC 60793-2-10 Type A1a.2 Ed.2.0, IEC 60793-1-49 Ed.2.0, ITU-T G.651, ISO/IEC 11801 Ed.2.2 Cat. OM3
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Fiber Count	2
Outer Jacket Color	Aqua

Mechanical Specifications	
Minimum Bend Radius	10 mm (0.39 in)
Nominal Outer Diameter	2 mm (0.08 in)

Edge Uniboot Jumper Standard LC Uniboot MM / Standard LC Uniboot MM, OM4 50um, 2F, DFX 250 Riser, Standard Aqua Jacket 5 Meters



Optical Characteristics	
Fiber Code	Q
Fiber Type	Multimode
Fiber Compliance	IEC 60793-2-10 for A1a class 50/125 multimode fibers; TIA/EIA 492AAAD (OM4); ITU-T Recommendation G.651; ISO/IEC 11801 Ed.2.2 Grade OM4
Fiber Core Diameter	50 µm
Minimum Effective Modal Bandwidth (EMB)	4700 MHz*km / -
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Min. Overfilled Launch (OFL) Bandwidth	1500 MHz*km / 500 MHz*km
Serial 1 Gigabit Ethernet	1000 MHz*km / 600 MHz*km
Serial 10 Gigabit Ethernet	600 MHz*km / -
Wavelengths	850 nm / 1300 nm
Fiber Category	OM4 Extended Distance

Specifications - Connector A	
Boot Color	Aqua
Connector Type	LC Uniboot
Ferrule Material	Ceramic
Housing Color	Black
Housing Material	Composite

Specifications - Connector B	
Boot Color	Aqua
Connector Type	LC Uniboot
Ferrule Material	Ceramic
Housing Color	Black

Edge Uniboot Jumper Standard LC Uniboot MM / Standard LC Uniboot MM, OM4 50um, 2F, DFX 250 Riser, Standard Aqua Jacket 5 Meters



Dimensions

Length	0 mm (0 in)
--------	-------------

Ordering Information

Product Number	797902QD120005M
EAN Code	4056418169934
Units per Delivery	1/1

Furcation - Connector A

Leg Length	0 mm (0 in)
------------	-------------

Furcation - Connector B

Leg Length	0 mm (0 in)
------------	-------------



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2025 Corning Optical Communications. All rights reserved.