Pulse Start Metal Halide Light Fixture



Ericson's LED Low-voltage Spot and Flood Lights provide uncompromised safety and performance by combining wet location use, OSHA compliance, rugged construction, and energy efficient LED technology in a lightweight package.

Multiple beam angles are combined with cool white LED illumination to reduce eye stress and improve visual acuity, thus greatly enhancing the work space enviroment. Designed for years of trouble free operation, the long-life LED lights are enclosed within a shatter resistant barrier supported by a rugged, non-conductive, corrosion resistant handle assembly.

Ideal for indoor and outdoor wet location use, the in-line power transformer provides an additional level of safety and electrical shock protection by delivering low voltage at the handle assembly. Additionally, multiple configuration alternatives provide a single lighting solution that can be tailored to specific application requirements.

info@ericson.com www.ericson.com

ERICSON
SAFETY IS OUR STANDARD

Standard Product Features:

- cULus Listed - Suitable For damp Locations
- Pulse Start Ballast Meets The Requirements Of The Energy Independence Act of 2017
- Open-Air Ballast For Cooler Operation
- Multi-Tap Ballast: 120 V, 208V, 240V, 277V: Factory Wired At 120 V
- Base Models Have 3 ft 18/3 Power Cord With 5-15P Molded Plug.
- Clear Metal Halide Pulse Type O Lamp Included (NEC 2008 Compliant)
- Average Rated Lamp L ife Of Over 10,000 Hours
- Super Bright Metal Halide Lamp Has A Color Temperature Of 4000K
- Easy Hook With Locking Feature - Fixture Mounts In Seconds, No Tools Required
- (2) ¾" Knock-Outs For Optional Conduit Access
- Double Envelope Bulb Stops Ruptures At End Of Life
- Heavy Duty Steel, Powder Coated Enclosure
- Easy Internal Taps For 208, 240, 277 Volts

Catalog Number	Description
1004-MHX-LPS	Type O 400W M155 E Pulse Start Bulb
1002-MHX-LPS	Type O 250W M155 E Pulse Start Bulb
1004-MHX-G	Wire guard for 1004-MHXPS
1004-MHX-BG	Bottom snap-on guard

See page two for Specifications

Specifications:

Catalog Number	Wattage	Guard	Primary Feed	Secondary Feed
1004-MHXPS	400	Open Cage	18/3 3ft 5-15P	N/A
1002-MHXPS	250	Open Cage	18/3 1ft 5-15P	N/A

Notes:
Sold in 2 pack cartons- add"-2" to each order.

100 YEARS STRONG ERICSON

Ericson Manufacturing Company
4323 Hamann Parkway
Willoughby, OH 44094, U.S.A

1.800.374.2766
info@ericson.com
www.ericson.com