



Lock lubricant

Lubricant

Long duration, oil-free lubrication.



1. General description

Lubricant for micro-mechanisms.

2. Characteristics

- Very strong penetration capability which allows the lock lubricant to reach all the cracks of the micro-mechanisms.
- Shows anti-corrosion action over a period of time.
- Recommended to lubricate locks, lock cylinders and inserts, micro-mechanisms in general.
- Does not harm the material that it comes in contact with in any way.
- The propellant of the aerosol is non-flammable carbon dioxide which allows having 95% of the active ingredient

3. Applications

Locks (cylinders or inserts). Mechanisms in general where use of oil or grease is not recommended.

4. Operating instructions

Shake the sprayer well before use.
Fix the capillary on the diffuser. Spray in short bursts on desired places.

A material safety data sheet (MSDS) compliant to the EC regulation No. 1907/2006 Art.31 and amendments is available for all KF products.

5. Typical characteristics of the product

Appearance	:liquid.
Colour	:Colourless.
Smell	: light hydrocarbon.
Specific gravity	:0.76.
Dynamic viscosity at 20 °C	: 2.5 mPa.s.



CRC Industries France SAS
12, Bld des Martyrs de Chateaubriant – Z.I. du Val d'Argent – B.P. 90028
F-95102 Argenteuil Cedex. - France
Tél.: + 33 (0)1 34 11 20 00 Fax.:+ 33 (0)1 34 11 09 96
S.A au capital de 1.936.667 € - R.C.S. Pontoise B 391 513 314 – APE 515 L
www.crcind.com





Lock lubricant

Lubricant

Long duration, oil-free lubrication.

Surface tension:	20.5 mN/m
p:H	5.5 to 7.
Drying time dry to touch:	3 min (evaporation of solvents)
Freezing point after evaporation	: - 35 °C.
Corrosion test on copper strip:	no change.

6. Packagings

Ref.: 6100 - Aerosol 140 ml gross - 100 ml net. carton of 12 aerosols.

All the data in this publication is based on laboratory experiments and tests. In view of the wide variety of conditions and devices used, as well as the unforeseeable human factors that could have an important influence on the results of the application, we advice you to ensure the compatibility of the product before using it. All this information is given as objectively as possible, but without any guarantee, expressed or implied, on our part.

This data sheet can always, even at this moment, be revised for reasons related to the legislation, availability of components or to newly acquired knowledge. The latest version of this data sheet, which is the only one that is valid, shall be sent to you on request, or can be found on our website: www.crcind.com.

We recommend you to register yourself on our website for this product, in order to receive every updated version of this document automatically.

Version: 6100 03 0212 05
Date: 17 February 2012



CRC Industries France SAS
12, Bld des Martyrs de Chateaubriant – Z.I. du Val d'Argent – B.P. 90028
F-95102 Argenteuil Cedex. - France
Tél.: + 33 (0)1 34 11 20 00 Fax.:+ 33 (0)1 34 11 09 96
S.A au capital de 1.936.667 € - R.C.S. Pontoise B 391 513 314 – APE 515 L
www.crcind.com

