



BUTT SET, TELEMATE 700 (POS) (TM-700)

Tele-Mate Pro, TM700 (POS) Telephone Test Set with
ABN clips and RJ11 lead (Point of Sale, POS box)

Cat No: 52061409

UPC No: 783310009849

Description

- LCD (96 x 48 pixels, 5 lines) displays the following: Caller ID (name and number) and Call Waiting
- Dialed number
- Over-voltage conditions
- Phone status (monitor, on hook etc.)
- Line Voltage: 110 Vdc max
- Loop Current: 125 mA max
- Ring Frequency: 15–70 Hz. High impedance monitor enables use on DSL line.
- Ergonomic shape.
- 32 digit memories.
- 10 x speed dial memories plus ten "last number redial" stores.
- Over voltage and over current protection and warning.
- Tone and pulse dialling for versatility.
- Flash key for timed-break recall.
- Pause which can be stored.
- Headset included for hands-free operation (HS-001).
- RJ11 socked and anchorage for strain relieved cords.
- Several cord options CS-01, CS-02, CS-03, CS-04, CS-05, CS-06, CS-07.
- Cordset with large "angled nose with bed-of-nails and spike" plus RJ11 plug.

Specifications

- Application : Test Telephone with High-impedance monitor, LCD, Smart Intercom, Calling Line ID, Pair tracing toner, DTMF decoding, Multiple last-number redial and ten speed-dial memories
- DC Voltage : TNV-3 working, 500 V peak, 1500 V TRANSIENT
- Dimensions : 9.25 (235 MM) Length X 2.5 (64 MM) Width X 3.25 (83 MM) Height
- Leakage : > 10 M ohms
- Loop Current :
 $< 10 \text{ mA} < I < 125 \text{ mA}$
- Replacement Part : Replaces PE830, Spares CS-01, CS-02, CS-03, CS-04, CS-05, CS-06, CS-07, HS-001
- Standard : TIA/EIA-470-B and ETSI
- Storage/Operating Temperature : -10 C to +70 C, <95% humidity storage, 0 C to +50 C, <90 % humidity (no condensation) operating
- Sub Brand : Tele-Mate
- Type : Tele-Mate Pro
- Voltage Measurement : 110 V dc max