

Type G

Type G
90°C - 2000 Volt - UL

Flexible and Portable Cord



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Fully annealed stranded bare copper, ropelay stranding for maximum flexibility

Category Insulation Description:

- EPDM for use up to 90°C

Category Jacket Description:

- Heavy duty thermoset CPE

Applications:

- Mining equipment, cranes, conveyors, and mobile equipment
- Excellent impact resistance
- Withstands severe environmental conditions
- Resistant to heat, acids, oil, moisture, and most chemicals

Standards:

- ICEA 5-75-381
- MSHA Approved

PART NUMBER TABLE							
Part#	Gauge	Conductors	Stranding	Ground Gauge	Insulation Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
B60804	8	4	133	4 # 12	0.06	1.045	690
B60604	6	4	259	4 # 12	0.06	1.125	880
B60404	4	4	259	4 # 10	0.06	1.225	1160
B60204	2	4	259	4 # 9	0.06	1.435	1720
B60104	1	4	259	4 # 8	0.06	1.595	2200
B61/004	1/0	4	259	4 # 7	0.06	1.73	2705
B62/004	2/0	4	259	4 # 6	0.08	1.855	3190
B63/004	3/0	4	259	4 # 5	0.08	2.04	4005
B64/004	4/0	4	259	4 # 4	0.08	2.145	4560
B625004	250	4	427	4 # 3	0.095	2.77	7143
B635004	350	4	888	4 # 2	0.095	3.1	6567
B650004	500	4	1235	4 # 1/0	0.095	3.4	10822

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
 Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
 Seattle • St. Louis • Tampa • Toronto
 © 2020 Omni Cable LLC