

Technique™ showcases the intricate veining in natural stone. Offered in contemporary colors it will add charm to any installation.

TECHNIQUE™

Glazed Porcelain



FLOOR / WALL

RESIDENTIAL

COMMERCIAL

INDOOR

OUTDOOR

POOL



Bianco



Ivory



Dove



Carbon

Mosaics



Bianco



Ivory



Dove



Carbon

| | | | | | | | | | |
|----------------------------|------------------------------|--|---------------------------|-----------------------------------|--------------------------|--------------------|--------------------------|---------------------------|--|
| SIZES | | | | | | | | | |
| | 12" x 24" 12.2" x 24.02" | | | 12" x 12" Mesh 11.71" x 11.71" | | | 3" x 12" Floor SBN | | |
| | 9mm | | | 9.5mm | | | 9mm | | |
| | 16 | | | N/A | | | N/A | | |
| | Matte | | | Matte | | | Matte | | |
| | Pressed | | | Cut | | | Cut/Rounded | | |
| Grout Joint Recommendation | 1/8" | | | 1/8" | | | 1/8" | | |
| | | | | | | | | | |
| Testing | Abrasion Resistance C1027 | | Breaking Strength C648 | Chemical Resistance C650 | Water Absorption C373 | DCOF ANSI A1371 | Scratch Hardness MOHS | Shade Variation Rating | |
| | IV | | >375 lbf | Resistant | <0.50% | >0.60 | 7 | V2 | |

Product and Installation Details | ANSI A108.02
Section 4.3.8.2 - For running bond/brick joint patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



- Sustainability Attributes
 - Red List Free
 - Health Product Declaration (HPD) provided upon request
 - Product Packaging is 100% recyclable
- VOC Free

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.