

## ACRO™ C-2

### THE ACRO™ ADVANTAGE

The Acro™ C-2 is the next generation of pistol mounted optics from Aimpoint. Built to endure the extreme demands of semi-automatic pistols, rifles and shotguns, the ACRO C-2 uses the proven closed emitter design enhanced with the CR2032 battery – achieving over 5 years of constant-on use. Aimpoint revolutionized red dot pistol optics as the creator of the first closed optical channel sight – establishing a new category of pistol optics. The ACRO C-2 is tested to withstand G-Force shock, vibration, temperature changes, and material stress generated by firing over 20,000 rounds of .40 S&W ammunition. A wide range of mounting solutions are available and when combined with the Micro™ interface mount plate it can be mounted with all MICRO mounts.

<b>ITEM NO.</b>	200692
<b>DOT SIZE</b>	3.5 MOA
<b>BATTERY TYPE</b>	CR2032
<b>BATTERY LIFE</b>	5 years (50,000 hours)

#### FULLY ENCLOSED DESIGN

Optical channel is completely sealed from environmental elements and contaminants. Submersible to 5 meters (15 feet).

#### FLUSH-MOUNTED WINDAGE & ELEVATION ADJUSTMENTS

Clicks you can hear and feel with each turn. Easily zeroed with the included Aimpoint® Tool (T10).

#### VARIETY OF MOUNTING SOLUTIONS

Mount plates for most optic-ready pistols. Mounting options for carbines, shotguns, rifles.

#### HARDENED FRONT & REAR LENSES

Protects reflective front lens and LED emitter. Recessed edges allow for flip-up lens covers (available as accessories) when used with a carbine, shotgun, or rifle.



#### DESIGNED FOR SPEED

Three-dimensional orientation allows for extremely quick/accurate target alignment. Shortens the training curve for new shooters.

#### ANODIZED ALUMINUM HOUSING

7075-T6 High-strength non-reflective anodized aluminum. Ultra compact, sleek design allows for ease of unholstering under concealment.

#### QUICK ACCESS BATTERY CAP

5 Years of constant-on use. Ability to change battery without removing sight from pistol.

#### DIGITAL INTENSITY BUTTONS

Brightness settings: 1-2 NVD, 3-10 daylight. Easy to use with gloves. Intuitive design.



## TECHNICAL SPECIFICATIONS

### OPTICAL SPECIFICATIONS

**Operating Principle:** Reflex collimator sight with LED

**Magnification:** 1X - No magnification

**Dot Size:** 3.5 MOA

**Dot Color:** Red

**Light Source Wavelength:** 650 nm red light

**NVD Compatible:** Yes

**Optical Coating:** Anti-reflex, all surfaces and multi-layer coating objective lens

**Clear Aperture:** 15 x 15 mm / 0.59 x 0.59 in

**Eye Relief:** Unlimited

**Transmission:** Average 60% in the range 420 - 700 nm

**Parallax:** Operationally parallax free - No centering required

### POWER SOURCE SPECIFICATIONS

**Battery Type:** CR2032 3 V, Lithium

**Battery Life:** 5 years (50,000h) of continuous use at daylight setting 6 (15,000 Lux, room temperature)

**Power Switch:** Push buttons

**Power Intensity:** 2 NVD and 8 daylight (DL), of which 1 extra bright

**Start Setting:** Position 7 of 10

### PHYSICAL SPECIFICATIONS

**Size L x W x H (mm) - Sight Only:**  
47 x 33 x 31 mm / 1.9 x 1.3 x 1.2 in

**Weight - Sight Only:** 61 g / 2.2 oz

**Housing Color:** Black

**Housing Surface Finish:** Anodized, semi-matte

**Housing Material:** High strength aluminum

**Height of Optical Axis:** 14 mm / 0.6 in  
Measured from top surface of mounting platform

**Adjustment Range:** ±1 m at 100 m / ±1 yd at 100 yds in windage and elevation

**Adjustment:** 1 click = 20 mm at 100 m / 0.7 in at 100 yds

**Lens Covers:** Not included - sold separately

### ENVIRONMENTAL SPECIFICATIONS

**Submersible:** 5 m / 15 ft

**Temperature Range Operation:**  
-30°C to +60°C / -20°F to +140°F

**Temperature Range Storage:**  
-51°C to +71°C / -60°F to +160°F

**Humidity:** Operable during and after humidity. Limits:  
RH: 95%, Temp: +20°C to +50°C / +68°F to +122°F, cyclic

**Shock:** Tested with 20,000 rounds mounted on a .40 S&W caliber pistol slide

**Vibration:** Withstands Vibration. Limits:  
Vibration, sinusoidal in a frequency range of 10 - 150 Hz.  
Frequency: 10 - 30 Hz, ±1.587 mm,  
Frequency: 30 - 150 Hz, 5.75 g, 1 octave/min.  
Direction: X, Y and Z, Time: 30 min/direction.

**Chemical Resistance:** Withstands occasional contamination by weapons cleaners, lubricants, fuels and insect repellents.

### MOUNTING SPECIFICATIONS

**Mounting Solution:** Integrated Acro™ interface

**Torque (mount to sight):** 3.0 Nm / 27 in-lbs

**Mounting Platform:** Acro™ interface

**Torque (mount to rail):** 1.25 Nm / 11 in-lbs