



SECTION A-A

STATIC TORQUE RECOMMENDATION: 25-43 in-lbs  
 REQUIREMENT MAY VARY DEPENDING UPON CONTAINER MATERIAL,  
 NECK FINISH, AND CAPPING EQUIPMENT

| REFERENCE                  | DIMENSION          | TOLERANCE           | UNITS                   |
|----------------------------|--------------------|---------------------|-------------------------|
| $\phi E$                   | 2.376 [60.35]      | $\pm 0.012$ [0.30]  | in [mm]                 |
| $\phi T'$                  | 2.467 [62.66]      | $\pm 0.012$ [0.30]  | in [mm]                 |
| H                          | 0.635 [16.13]      | $\pm 0.010$ [0.25]  | in [mm]                 |
| OAH                        | 0.725 [18.42]      | $\pm 0.016$ [0.25]  | in [mm]                 |
| $\phi OD$                  | 2.590 [65.79]      | $\pm 0.010$ [0.25]  | in [mm]                 |
| PART WEIGHT                | 10.00              | $\pm 0.75$          | g                       |
|                            |                    |                     |                         |
|                            |                    |                     |                         |
|                            |                    |                     |                         |
|                            |                    |                     |                         |
| THREAD DETAIL INFORMATION: | 6 THREADS PER INCH | 0.167" [4.24] PITCH | 380° FULL DEPTH THREADS |

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG31443

DESCRIPTION:

63-485 White PP Spice Cap with PS113 Liner

# Uni-Foam<sup>TM</sup> Technical Data Sheet

## PS-113 (Pressure Sensitive)

Revision: PS-113-12022013

| <b>Product</b>  | PS-113 (Pressure Sensitive)  |          |          |        |                  |        |          |                |        |          |  |  |
|---|--|----------|----------|--------|------------------|--------|----------|----------------|--------|----------|--|--|
| <b>Scope</b>  | One piece uniform polystyrene foam coated on one side with a specially formulated torque-activated adhesive. (Not approved for use with wet products.)   |          |          |        |                  |        |          |                |        |          |  |  |
| <b>Composition</b>  | <table border="1"> <thead> <tr> <th>Material</th> <th>Standard</th> <th>Metric</th> </tr> </thead> <tbody> <tr> <td>Polystyrene Foam</td> <td>0.020"</td> <td>0.508 mm</td> </tr> <tr> <td>Adhesive Layer</td> <td>0.002"</td> <td>0.051 mm</td> </tr> </tbody> </table> | Material | Standard | Metric | Polystyrene Foam | 0.020" | 0.508 mm | Adhesive Layer | 0.002" | 0.051 mm |  |  |
| Material  | Standard   | Metric   |          |        |                  |        |          |                |        |          |  |  |
| Polystyrene Foam  | 0.020"   | 0.508 mm |          |        |                  |        |          |                |        |          |  |  |
| Adhesive Layer  | 0.002"   | 0.051 mm |          |        |                  |        |          |                |        |          |  |  |
| <b>FDA Status:</b> 21 CFR 177.1210                          | <b>Recommended Storage and Handling:</b> Refer to website  |          |          |        |                  |        |          |                |        |          |  |  |
| <b>Drug Master File (DMF):</b> 3948                         | <b>EU / EP Reg.:</b>   |          |          |        |                  |        |          |                |        |          |  |  |
| <b>GTR Oxygen:</b> 2290 cc/m <sup>2</sup> .Day (ASTM D3985) | <b>MVTR:</b> 5.85 g/m <sup>2</sup> .Day (ASTM F1249)   |          |          |        |                  |        |          |                |        |          |  |  |
| <b>Print Location (if any):</b>                             |  |          |          |        |                  |        |          |                |        |          |  |  |

Selig materials are compliant with limitation of heavy metals in packaging per CONEG & EU 94/62/EC, article 11.

MSDS's are not required as Selig is not a chemical manufacturer or distributor and our products are 'articles' intended for food packaging per 29 CFR 1910.1200 (HazCom).

Page 2 of 2

DISTRIBUTED BY:



REF NO.:

DWG31443

DESCRIPTION:

63-485 White PP Spice Cap with PS113 Liner

**DISCLAIMER**

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.