## HUBBELL Wiring Device-Kellems

Replaced by HBL5362STW, Straight Blade Devices, Receptacles, Duplex, Commercial Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, White, Single Pack

By Hubbell Wiring Device-Kellems Catalog # HBL5342W

Straight Blade Devices, Receptacles, Duplex, Commercial Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, White, Single Pack.



## General

Application Extra Heavy Duty Compact

HBL5342W

White Color **EU RoHS Indicator** Yes

**Environmental Conditions** 

Additional Means

Traditional Duplex

- Certified for current

interrupting at full rated

Horsepower - Maximum

Item Type

Material - Mounting Hardware Screw Mounting

Number Of Poles

Catalog Number

Operating Temperature

Performance

Indoor Dry Unless Protected By

Industry Standard(s)

**Certifications And Compliance** 

Conductor Related

Number Of Wires

Wire Size

Certified to CSA 22.2, No. 42

File 285

3-Wire

Fed. Spec. WC596

NEMA® WD-6 Compliant

#12 AWG to #10 AWG

UL Listed to UL498 File No.

E2186

5-20R Nema Rating

Logistics

Carton Quantity 10

**Product Assets** 

Catalogs - WDK Catalog Full 2024

Warranty - Industrial & Commercial Products

current

2-Pole

Electrical - Dielectric Voltage -Withstands 2,000V minimum

Maximum continuous 75°C and

minimum -40°C without Impact

Electrical - Current Interrupting

Environmental - Flammability -Top: UL 94V-2, Base: UL 94V-0

Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)

Mechanical - Product

Identification - Ratings are a permanent part of the device

Mechanical - Terminal Accommodation - #12-#10 AWG stranded or solid copper

wire only

Mechanical - Terminal Identification - Terminals identified in accordance with

UL 498 and CSA

Series Heavy Duty

Finder Groove Face Style Type Standard Duplex 783585434827 **UPC** 

Dimensions

Dimensions 3.28 in x 1.33 in x 1.05 in Standard Sized Product Display Size

Height 1.05 in Length 3.28 in 0.2 lb Weight Width 1.33 in

**Electrical Ratings** 


Amperage Rating 20 A

Side Wired Only Connectivity

Current / Amperage Rating 20 A Current Rating 20 A

Withstands 2,000V minimum Dielectric Strength

Phase Single Phase 125 VAC Voltage Rating Voltage Rating Description 125 V 2500 W Wattage



©2024 Hubbell Incorporated. All rights reserved WDK\_MX-HBL5342W-SPEC-EN | REV 6/2024