

DIGITAL MASTER MIXING VALVE CROSS CHART

Pipe Size	Powers IntelliStation 2®	Armstrong® The Brain®	Leonard® Nucleus	Leonard® Proton	Symmons® TempControl Digital
3/4"	IS2075VL 34-125 GPM	DRV25* 0-19 GPM	N/A	PPV-075-LF† 2-70 GPM	E200/E200C/E200CPS‡ 27 GPM @10 psi
1"	IS2100VL 51-171 GPM	N/A	N/A	PNV-100-LF 17-51 GPM	E400/E400C/E400CPS‡ 53 GPM @10 psi
1-1/4"	IS2100VL 51-171 GPM	N/A	N/A	PNV-125-LF 40-120 GPM	E500/E500C/E500CPS‡ 70 GPM @10 psi
1-1/2"	IS2150VL 78-251 GPM	DRV40 0-41 GPM	NV-150-LF 50-165 GPM	PNV-150-LF 50-165 GPM	E900/E900C/E900CPS‡ 104 GPM @10 psi
2"	IS2200VL 100-332 GPM	DRV50 0-73 GPM	NV-200-LF 80-226 GPM	PNV-200-LF 80-226 GPM	E1000/E1000C/E1000CPS‡ 140 GPM @10 psi

NOTES:

* **Armstrong:** Model DRV25 is Armstrong's smallest Brain model (0-19 GPM); not a direct 3/4" pipe-size match.

† **Leonard:** Model PPV-075-LF is the Proton Plus high-flow variant, distinct from the standard PNV Proton series.

‡ **Symmons:** TempControl Digital offers complete valve and cartridge models with a range of options, as well as individual digital cartridges designed for retrofit in existing TempControl 7-Series thermostatic valve bodies.

Modifiers: C = Connect 3-year subscription with TCDKIT, CPS = Connect+ 3-year subscription with TCDCPSKIT.

N/A: Size not offered in that product line.

GPM ranges are manufacturer-published flow rates and vary by pressure drop/configuration; confirm exact figures against current product specifications before quoting or specifying.

SYMMONS TEMPCONTROL DIGITAL

SIMPLE TO SPECIFY

A code-compliant digital valve that's easy to size and built for long-term reliability.

EFFORTLESS TO CONTROL

Greater visibility, safety, and energy savings with app-based control and monitoring.

QUICK TO RESPOND

Shorten your team's response time through real-time notifications directly to staff.

Learn more at: symmons.com/tempcontrol-digital