31/4" ROUND CEILING PANST - 4.0 CUBIC INCH CAPACITY

1/2" DEEP CLAMPS IN BOTTOM FIXTURE RATED UL LISTED



TP266

	Knockouts		——— Unit	Wt. Lbs.	Wt lhe	
Cat. #	Cable	Conduit	Qty.	Per 100		
TP266	4 - Cable	1 - 1/2"	50	30		

†Weight limit for 31/4" and 4" Octagon Outlet Boxes and Ceiling Pans is 50 lbs. for fixture/luminaire. Not suitable for fans.

31/4" OCTAGON OUTLET BOXEST - 9.0 CUBIC INCH CAPACITY

1½" DEEP FIXTURE RATED UL LISTED











TP256

TP259

TP260

TP264

	Knockouts		_ Unit	Wt. Lbs.
Description	Sides	Bottom	Qty.	Per 100
-	4 - 1/2"	1 - 1/2"	50	41
Extension Ring	4 - 1/2"	-	50	31
th Clamps				
"S" Bracket, Set 1/2"	4 - Cable, 1 - ½"	1 - 1/2"	50	53
-	4 - Cable, 2 - ½"	1 - 1/2"	50	44
Two Screw Ears	4 - Cable, 2 - ½"	1 - 1/2"	50	47
	Extension Ring th Clamps "S" Bracket, Set ½"	- 4 - 1/2" Extension Ring 4 - 1/2" th Clamps "S" Bracket, Set 1/2" 4 - Cable, 1 - 1/2" - 4 - Cable, 2 - 1/2"	- 4 - ½" 1 - ½" Extension Ring 4 - ½" - th Clamps "S" Bracket, Set ½" 4 - Cable, 1 - ½" 1 - ½" - 4 - Cable, 2 - ½" 1 - ½"	Description Sides Bottom Oty. - 4 - ½" 1 - ½" 50 Extension Ring 4 - ½" - 50 th Clamps "S" Bracket, Set ½" 4 - Cable, 1 - ½" 1 - ½" 50 - 4 - Cable, 2 - ½" 1 - ½" 50

†Weight limit for 31/4" and 4" Octagon Outlet Boxes and Ceiling Pans is 50 lbs. for fixture/luminaire. Not suitable for fans.

31/4" ROUND CEILING COVERS

UL LISTED





TP270

TP272

	Knockouts	— Unit	Wt. Lbs.
Cat. #	Cable	Qty.	Per 100
TP270	Flat Blank	100	18
TP272	Flat, 1/2" KO in Center	100	18

4" ROUND CEILING PANS* - 6.0 CUBIC INCH CAPACITY

1/2" **DEEP FIXTURE RATED UL LISTED**







TP267

		Knockouts		— Unit	Wt. Lbs.
Cat. #	Description	Sides	Bottom	Oty.	Per 100
TP269	KOs Only	-	5 - 1/2"	50	35
TP267	KOs and Clamps	-	4 - Cable, 3 - ½"	50	39

^{*}Weight limit for 31/4" and 4" Octagon Outlet Boxes and Ceiling Pans is 50 lbs. for fixture. Not suitable for fans.

4" OCTAGON OUTLET BOXEST - 15.5 CUBIC INCH CAPACITY

FOR CONDUIT - NO CLAMPS **FIXTURE RATED**

UL LISTED



TP274, TP278, TP834*



TP276



TP273



TP280



TP282



TP284, TP286

Cat. #		Knockouts		Unit	Wt. Lbs.	
	Description	Sides	Bottom	Qty.	Per 100	
TP274	-	4 - 1/2"	5 - 1/2"	50	50	
TP273	Blank Bottom	4 - 1/2"	-	50	51	
TP276	-	4 - 3/4"	3 - 1/2", 2 - 3/4"	50	50	
TP278	-	2 - 1/2", 2 - 3/4"	3 - 1/2", 2 - 3/4"	50	50	
TP280	"C" Bracket	4 - 1/2"	5 - 1/2"	50	60	
TP282	"S" Bracket, Set ½"	3 - 1/2"	5 - 1/2"	50	58	
Air Plenum						
TP834*	For Air Plenum	4 - 1/2"	5 - 1/2"	50	52	
Octagon Extensi	on Rings - (Slot & Key Permit l	Mounting without Re	moving Box Screws)			
TP284‡	-	4 - 1/2"	-	50	36	
TP286‡	-	2 - 1/2", 2 - 3/4"	-	50	36	



^{*}For Air Plenum (no mounting holes) - not UL Listed. †Weight limit for 31/4" and 4" Octagon Outlet Boxes and Ceiling Pans is 50 lbs. for fixture/luminaire. Not suitable for fans. ‡CSA certified.

4" OCTAGON OUTLET BOXEST - 15.5 CUBIC INCH CAPACITY

FOR ARMOURED & METAL-CLAD (MCI) CABLE - CLAMPS IN EACH END **FIXTURE RATED**

UL LISTED







TP310 TP312

Vacalianta

TP314

		Knockouts		——— Unit	Wt. Lbs.	
Cat. #	Description	Sides	Bottom	Qty.	Per 100	
TP310*	-	4 - Cable, 2 - 1/2"	1 - 1/2"	50	57	
TP312*	"C" Bracket	4 - Cable, 2 - ½"	1 - 1/2"	50	66	
TP314*	"S" Bracket, Set ½"	4 - Cable, 1 - ½"	1 - 1/2"	50	64	

^{*}UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP"). MCAP" is a registered trademark of Southwire Company.

4" OCTAGON OUTLET BOXEST - 15.5 CUBIC INCH CAPACITY

11/2" DEEP FOR NON-METALLIC CABLE - WITH CLAMPS **FIXTURE RATED**

UL LISTED



TP298











TP308

TP306

		Knockouts		Unit	Wt. Lbs.	
Cat. #	Description	Sides	Bottom	Qty.	Per 100	
TP298	-	4 - Cable, 2 - 1/2"	1 - 1/2"	50	56	
TP300	With Side Nail Holes	4 - Cable, 2 - 1/2"	1 - 1/2"	50	55	
TP302	"C" Bracket	4 - Cable, 2 - ½"	1 - 1/2"	50	65	
TP304	"S" Bracket, Set 1/2"	4 - Cable, 1 - ½"	1 - 1/2"	50	64	
TP306	Two Screw Ears	4 - Cable, 2 - 1/2"	1 - 1/2"	50	58	
TP308	"F" Bracket, Set ½"	4 - Cable, 1 - 1/2"	1 - 1/2"	50	64	

†Weight limit for 31/4" and 4" Octagon Outlet Boxes and Ceiling Pans is 50 lbs. for fixture/luminaire. Not suitable for fans.



tWeight limit for 31/4" and 4" Octagon Outlet Boxes and Ceiling Pans is 50 lbs. for fixture/luminaire. Not suitable for fans.

4" OCTAGON OUTLET BOXEST - 21.5 CUBIC INCH CAPACITY

21/8" DEEP **FOR CONDUIT - NO CLAMPS FIXTURE RATED**

UL LISTED









TP288, TP290, TP294

TP292, TP838*

TP292RED

TP339

Cat. #		Knockouts		Unit	Wt. Lbs.
	Description	Sides	Bottom	Qty.	Per 100
TP288	-	4 - 1/2"	$3 - \frac{1}{2}''$, $2 - \frac{3}{4}''$	25	64
TP288PF‡	-	4 - 1/2"	$3 - \frac{1}{2}$, $2 - \frac{3}{4}$	25	64
TP290	=	4 - 3/4"	$3 - \frac{1}{2}$, $2 - \frac{3}{4}$	25	64
TP290PF‡	-	4 - 3/4"	$3 - \frac{1}{2}$, $2 - \frac{3}{4}$	25	64
TP292	-	2 - 1/2", 2 - 3/4"	$3 - \frac{1}{2}$, $2 - \frac{3}{4}$	25	64
TP292PF‡	-	2 - 1/2", 2 - 3/4"	$3 - \frac{1}{2}$, $2 - \frac{3}{4}$	25	64
TP292RED	=	2 - 1/2", 2 - 3/4"	$3 - \frac{1}{2}$, $2 - \frac{3}{4}$	25	64
TP294	-	4 - 1"	$3 - \frac{1}{2}$, $2 - \frac{3}{4}$	25	64
TP339	Blank Bottom	4 - 1/2"	-	25	65
Air Plenum					
TP838*	For Air Plenum	2 - 1/2", 2 - 3/4"	3 - 1/2", 2 - 3/4"	25	62

^{*}For Air Plenum (no mounting holes) - not UL Listed.

TWeight limit for 31." and 4" Octagon Outlet Boxes and Ceiling Pans is 50 lbs. for fixture/luminaire. Not suitable for fans. ‡TP catalog numbers ending in PF include ground screw with pigtail lead.

4" OCTAGON OUTLET BOXEST - 21.5 CUBIC INCH CAPACITY

21/8" DEEP - WITH CABLE CLAMPS **FIXTURE RATED**

UL LISTED











TP316

TP318

TP320

TP317 TP338

		Knockouts		——— Unit	Wt. Lbs.	
Cat. #	Description	Sides	Bottom	Qty.	Per 100	
For Non-metallic	Cable					
TP316	-	4 - Cable, 2 - 1/2"	1 - 1/2"	25	68	
TP318	"C" Bracket	4 - Cable, 2 - 1/2"	1 - 1/2"	25	88	
TP320	"S" Bracket, Set ½"	4 - Cable, 1 - ½"	1 - 1/2"	25	81	
For Armoured & N	Metal-clad (MCI) Cable – Clam	ps in Each End				
TP317*	-	4 - Cable, 2 - 1/2"	1 - 1/2"	25	69	
TP338*	"S" Bracket, Set 1/2"	4 - Cable, 1 - 1/2"	1 - 1/2"	25	82	
TP338PF‡	"S" Bracket, Set 1/2"	4 - Cable, 1 - 1/2"	1 - 1/2"	25	82	

^{*}UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP™).

MCAP^{**} is a registered trademark of Southwire Company.

†Weight limit for 3½" and 4" Octagon Outlet Boxes and Ceiling Pans is 50 lbs. for fixture/luminaire. Not suitable for fans. ‡TP catalog numbers ending in PF include ground screw with pigtail lead.

