

PRODUCTION GRADE BOX SEALING TAPE • SYSTEM LENGTH



DESCRIPTION

30 micron polypropylene film coated with 12% more aggressive high tack thermoplastic adhesive, 11% thicker and stronger than # 244. Resistant to various chemicals and corrosion. Excellent tear and impact resistance. 254 has an easy unwind which allow for smooth release from the roll and even lay down. Stock item in clear(00), tan(04) colour available on custom request. In USA only.

MAIN FEATURES

- Strength.
- High tack.
- Ease of application.
- Impact resistant.
- Water resistant.
- Easy unwind.
- Elongation.

APPLICATIONS

- Single Strips closure of regular slotted containers (RSC's) dispensed by automatic case sealer.

TECHNICAL DATA

Colour	Clear(00), Tan(04)
Backing	30 mic polypropylene film
Adhesive	Synthetic
Thickness	1.9 mil
Adhesion	32 oz/in
Tensile Strength.....	22 lb/in
Elongation	120%
Application Range.....	+7°C to 49°C (+45°F to 120°F)
Operating Range.....	-23°C to 60°C (-10°F to 140°F)

ELONGATION

TENSILE STRENGTH

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.