

CyberPower

MP1097WW 6-OUTLET WALL-TAP WITH USB AND NIGHT LIGHT MULTI-PACK

Power, surge protection and USB charging solutions for home and office electronics

The CyberPower MP1097WW two-pack Wall-tap Surge Protectors with USB charging safeguards common home and office devices, such as computers and electronics, by absorbing spikes in energy caused by storms and electrical power surges. Each unit provides 900 joules of protection, has 6 surge-protected AC outlets, two USB-A ports with 2.4 Amps shared power output and one USB-C port rated at 18W PD to charge mobile and USB enabled devices. The CyberPower MP1097WW two-pack feature a photo sensor activated light and an impact-resistant casing.

This surge protector wall-tap two-pack comes with a One-Year Limited Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 900 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- AC Outlets: 6
- Outlet type: NEMA 5-15R
- USB-A charge ports: 2
- USB-A charge output: 2.4A (shared)
- USB-C charge ports: 1
- USB-C charge output: 18W PD
- Adjustable Brightness Night Light
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$100,000

SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	Wall-tap
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Wall-tap

OUTPUT	
Outlet Type	6 - NEMA 5-15R
Outlets - Total	6
USB Charge Port	Yes
USB Charge Port Amperage	2.4 A (Shared)
USB Charge Port Quantity	3
USB Charge Port Type	2 x Type A 1 x Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	18 Watts



MP1097WW

6-OUTLET WALL-TAP WITH USB AND NIGHT LIGHT MULTI-PACK

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	800V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz 100 MHz
Maximum Surge Current	24,000 A
Maximum Surge Current H-G	8,000 A
Maximum Surge Current H-N	8,000 A
Maximum Surge Current N-G	8,000 A
Maximum Surge Voltage	6,000 A
Response Time	<1 Nanosecond
Surge Suppression (Joules)	900 J
PHYSICAL	
Color	White
Form Factor	Wall-tap
Form Factors Supported	Direct Plug
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	8.89 x 15.88 x 5.72 cm
Physical Dimensions - Width/Height/Depth (mm)	89 x 159 x 57 mm
Physical Dimensions - Width/Height/Depth (in.)	3.5 x 6.25 x 2.25 in.
Weight (kg)	0.33 kg
Weight (lb)	0.72 lbs.
Country of Origin	China

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	17.78 x 10.16 x 17.78 cm
Shipping Dimensions - Width/Height/Depth (mm)	177.8 x 101.6 x 177.8 mm
Shipping Dimensions - Width/Height/Depth (in)	7 x 4 x 7 in.
Weight (kg)	0.82 kg
Weight (lb)	1.80 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL498A, UL1449 4th Edition, FCC PART 15B, DOE VI
WARRANTY	
CEG Amount	\$100,000
Connected Equipment Guarantee	Lifetime
Product Warranty	One-Year Limited Warranty