


Bennington



Colors



Gray
VTL BNGY




Bronze
VTL BNBZ



Black
VTL BNBK

Sizes



12" x 24" x 8.2mm

- Gray
- Bronze
- Black

BENNINGTON

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
12" x 24"	11.75" x 23.6875"	8.2mm	Matte/Natural

* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
2" x 2" Mosaic (Black & Gray)	11.75" x 11.75"	Matte/Natural
2" x 2" Mosaic Rectified (Bronze)	11.75" x 11.75"	Matte/Natural
3" x 12" Bullnose Rectified (Bronze)	2.75" x 11.75"	Matte/Natural
4" x 12" Bullnose (Black & Gray)	4" x 11.75"	Matte/Natural

Recommended Grout Joint: 1/8" - Rectified
3/16" - Non Rectified

Product Characteristics

	MATTE/NATURAL
Breaking Strength (ASTM C648 or ISO 10545-4)	≥ 325lbs
Chemical Resistance (ASTM C650 or ISO 10545-13)	Class A
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	≤ 0.5%
Certifications	N/A
Country of Origin	USA
Shade Variation Code	V3

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Material

Porcelain



V3 Moderate Variation



Made in USA



Frost Resistant



DCOF: ≥ 0.42



Water Absorption: ≤ 0.5%



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
COMMERCIAL SURFACES