

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

# NRG 300 SERIES

PERIMETER WALL PACK

## FEATURES

- New higher output plus increased lumens per watt
- 5000K high 80 CRI LEDs provide optimal color recognition
- 1,800+ lumens at 110+ LPW
- Universal voltage 120-277V (including photocontrol)
- Non-cutoff retractor fills surrounding area with safety/security illumination
- ½ bottom knockout for surface conduit wiring
- Rigid cast aluminum back housing
- One-piece polycarbonate front
- Tamper proof hardware included



## SPECIFICATIONS

### CONSTRUCTION

- Full polycarbonate front provides vandal resistance and efficient spread of forward and lateral light coverage
- Internally painted bronze finish for lasting appearance
- LED unit is an excellent upgrade from HID systems featuring a 17w LED system with a 1700+ lumen output, 5000K CCT, 80 CRI - 60,500 hr rated life at L94
- Rugged cast aluminum back housing for rigid mounting; Bottom 1/2" conduit knockout for surface conduit wiring. Back hub allows access to recessed wiring boxes; Two point mounting; Additional center-pin torx screws provided for tamper-resistant applications

### OPTICS

- Single driver 50/60 Hz, 120-277V
- NRG-356L is 1794 lumens, 5000K, 110 IPW, CRI 80
- PC version 120V-277V

### CERTIFICATIONS

- Listed to UL 1598 for use in wet locations

### WARRANTY

- 5 Year warranty

tradeSELECT®



KEY DATA	
Lumen Range	1794
Wattage	16.6
Efficacy Range (LPW)	110
Weight lbs. (kg)	6 lbs. (2.7kg)

# NRG 300 SERIES

PERIMETER WALL PACK

## ORDERING INFORMATION

Catalog Number	Without Photocontrol	Wattage	Voltage	Max Input Amps	Color	Weight lbs. (kg)
	NRG-356L-5K-U	16.3W	120-277V	.15	Dark Bronze Matte Textured	6 (2.7)

## ACCESSORIES

Catalog Number	Description
PBT-1	Button photocontrol, 120V
PBT-234	Button photocontrol, 208, 240, 277V

## DIMENSIONS

